

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	13 Hour 10 Min 59 Sec
Total Counter :	1850748	Total Running Time :	723 Hour 5 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	127	%	Manual ;	66	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.15	kN	No		
HEP :	25.0 %	25.14	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.52	kN	Yes 15	Times	
Ref :		20.12	kN			
LCP :	2.0 %	19.71	kN	Yes 15	Times	
LEP :	25.0 %	15.09	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.08	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	0.60	kN	Min :	0.55	kN	Punch NO.;	23
SD :	3.10	%	Max :	0.63	kN	Punch NO.;	31
Mean Main Pressure :	19.41	kN	Min :	17.22	kN	Punch NO.;	23
SD :	5.00	%	Max :	21.57	kN	Punch NO.;	41
Filling Depth :	Increase ;	1664	Times	Decrease ;	1584	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	8.95	mm	Current Cam :	Cam C	
Main Air pressure :	0.788	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.29	kN	Max Punch ;	19
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	1850748	Tablets			
A.W.C Counter :	1825645	Tablets			
HEP :	1535 (0.1%)	Tablets	LEP :	686 (0.0%)	Tablets
GOOD :	1823424 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500140
Print Interval :	50000 Tablets	Running Time :	13 Hour 10 Min 59 Sec
Total Counter :	1850748	Total Running Time :	723 Hour 5 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	126	%	Manual ;	74	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.24	kN	No		
HEP :	25.0 %	25.23	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	20.58	kN	Yes 15	Times	
Ref :		20.18	kN			
LCP :	2.0 %	19.78	kN	Yes 15	Times	
LEP :	25.0 %	15.14	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	14.13	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	0.92	kN	Min :	0.86	kN	Punch NO.;	2
SD :	2.40	%	Max :	0.97	kN	Punch NO.;	7
Mean Main Pressure :	20.53	kN	Min :	18.53	kN	Punch NO.;	2
SD :	4.90	%	Max :	23.38	kN	Punch NO.;	7
Filling Depth :	Increase ;	1136	Times	Decrease ;	1003	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	25	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.70	mm	Pre Thickness ;	3.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	8.09	mm	Current Cam :	Cam C	
				8.5-14mm	
Main Air pressure :	0.788	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	23	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.29	kN	Max Punch ;	19
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	1850748	Tablets			
A.W.C Counter :	1825698	Tablets			
HEP :	1535 (0.1%)	Tablets	LEP :	686 (0.0%)	Tablets
GOOD :	1823477 (99.9%)	Tablets			