

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	am98755	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 54 Sec
Total Counter :	651802	Total Running Time :	730 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	105	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.67	kN	No		
HEP :	25.0 %	23.73	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	19.36	kN	Yes 15	Times	
Ref :		18.98	kN			
LCP :	2.0 %	18.60	kN	Yes 15	Times	
LEP :	25.0 %	14.24	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.29	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.81	kN	Min :	2.48	kN	Punch NO.;	33
SD :	4.90	%	Max :	3.23	kN	Punch NO.;	39
Mean Main Pressure :	19.29	kN	Min :	17.61	kN	Punch NO.;	33
SD :	3.60	%	Max :	21.16	kN	Punch NO.;	39
Filling Depth :	Increase ; 189	Times	Decrease ;	196	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	19	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.69	mm	Pre Thickness ;	1.70	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.83	mm	Main Thickness ;	0.84	mm
Filling Depth :	5.90	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.795	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.08	kN	Max Punch ;	52
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	49
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	651802	Tablets			
A.W.C Counter :	635997	Tablets			
HEP :	512 (0.1%)	Tablets	LEP :	493 (0.1%)	Tablets
GOOD :	634992 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	am98755	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	05 Hour 48 Min 54 Sec
Total Counter :	651802	Total Running Time :	730 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	96	%	Manual ;	32	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.33	kN	No		
HEP :	25.0 %	25.32	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	20.66	kN	Yes	15	Times
Ref :		20.26	kN			
LCP :	2.0 %	19.85	kN	Yes	15	Times
LEP :	25.0 %	15.19	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	14.18	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.65	kN	Min :	2.34	kN	Punch NO.;	33
		5.40	%	Max :	2.99	kN	Punch NO.;	17
Mean Main Pressure :		19.76	kN	Min :	18.09	kN	Punch NO.;	33
	SD :	3.20	%	Max :	20.92	kN	Punch NO.;	39
Filling Depth :	Increase ;	160	Times	Decrease ;	158	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	5.98	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.795	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	4	Min			
Lower Punch Remain Time (S2):	29	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	53
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	49
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	651802	Tablets			
A.W.C Counter :	635997	Tablets			
HEP :	512 (0.1%)	Tablets	LEP :	493 (0.1%)	Tablets
GOOD :	634992 (99.8%)	Tablets			