

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	am98755	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	09 Hour 00 Min 33 Sec
Total Counter :	1001878	Total Running Time :	733 Hour 12 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	96	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.73	kN	No		
HEP :	25.0 %	23.78	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	19.50	kN	Yes 15	Times	
Ref :		19.03	kN			
LCP :	2.5 %	18.55	kN	Yes 15	Times	
LEP :	25.0 %	14.27	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.32	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.85	kN	Min :	2.56	kN	Punch NO.;	16
SD :	5.00	%	Max :	3.25	kN	Punch NO.;	44
Mean Main Pressure :	19.29	kN	Min :	17.69	kN	Punch NO.;	20
SD :	3.70	%	Max :	21.01	kN	Punch NO.;	44
Filling Depth :	Increase ;	425	Times	Decrease ;	418	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.69	mm	Pre Thickness ;	1.70	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	6.40	mm	Current Cam :	Cam B	
Main Air pressure :	0.798	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	1001878	Tablets			
A.W.C Counter :	984215	Tablets			
HEP :	741 (0.1%)	Tablets	LEP :	558 (0.1%)	Tablets
GOOD :	982916 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name : VANTIX P720D User ID : am98755 Print Interval : 50000 Tablets Total Counter : 1001878 Station : Station 2	Product Name : Amioda 200mgSTAl3A00 Batch NO. : AIM2500220 Running Time : 09 Hour 00 Min 33 Sec Total Running Time : 733 Hour 12 Min
---	---

Setting Value

Feeder :	Auto ;	90	%	Manual ;	32	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		1500000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	24.89	kN	No		
HEP :	25.0 %	23.94	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	19.63	kN	Yes 15	Times	
Ref :		19.15	kN			
LCP :	2.5 %	18.67	kN	Yes 15	Times	
LEP :	25.0 %	14.36	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.40	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.94	kN	Min :	2.56	kN	Punch NO.;	33
		5.80	%	Max :	3.43	kN	Punch NO.;	36
Mean Main Pressure :		19.21	kN	Min :	17.77	kN	Punch NO.;	33
	SD :	3.50	%	Max :	20.88	kN	Punch NO.;	36
Filling Depth :	Increase ;	328	Times	Decrease ;	324	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	15	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.94	mm	Main Thickness ;	0.95	mm
Filling Depth :	6.25	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.798	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	15	Min			
Lower Punch Remain Time (S2):	20	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	1001878	Tablets			
A.W.C Counter :	984215	Tablets			
HEP :	741 (0.1%)	Tablets	LEP :	558 (0.1%)	Tablets
GOOD :	982916 (99.9%)	Tablets			