

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	pb97604	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	12 Hour 15 Min 11 Sec
Total Counter :	1351994	Total Running Time :	736 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	99	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		1500000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.78	kN	No		
HEP :	25.0 %	24.79	kN	Yes	10	Rotations 15 Tablets
HCP :	2.5 %	20.33	kN	Yes	15	Times
Ref :		19.83	kN			
LCP :	2.5 %	19.34	kN	Yes	15	Times
LEP :	25.0 %	14.88	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	13.88	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.99	kN	Min :	2.74	kN	Punch NO.;	18
SD :	4.00	%	Max :	3.22	kN	Punch NO.;	6
Mean Main Pressure :	19.79	kN	Min :	18.20	kN	Punch NO.;	18
SD :	3.00	%	Max :	20.96	kN	Punch NO.;	46
Filling Depth :	Increase ;	713	Times	Decrease ;	699	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.69	mm	Pre Thickness ;	1.70	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	5.67	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	53
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	1351994	Tablets			
A.W.C Counter :	1331990	Tablets			
HEP :	1063 (0.1%)	Tablets	LEP :	558 (0.0%)	Tablets
GOOD :	1330369 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	pb97604	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	12 Hour 15 Min 11 Sec
Total Counter :	1351994	Total Running Time :	736 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	95	%	Manual ;	32	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.90	kN	No		
HEP :	25.0 %	22.98	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	18.84	kN	Yes 15	Times	
Ref :		18.39	kN			
LCP :	2.5 %	17.93	kN	Yes 15	Times	
LEP :	25.0 %	13.79	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.87	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.84	kN	Min :	2.42	kN	Punch NO.;	20
SD :	5.90	%	Max :	3.16	kN	Punch NO.;	9
Mean Main Pressure :	18.39	kN	Min :	16.50	kN	Punch NO.;	20
SD :	3.70	%	Max :	19.99	kN	Punch NO.;	49
Filling Depth :	Increase ;	481	Times	Decrease ;	481	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.97	mm	Main Thickness ;	0.98	mm
Filling Depth :	6.16	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.796	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	13	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	53
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	1351994	Tablets			
A.W.C Counter :	1331990	Tablets			
HEP :	1063 (0.1%)	Tablets	LEP :	558 (0.0%)	Tablets
GOOD :	1330369 (99.9%)	Tablets			