

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	gp98929	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	13 Hour 07 Min 36 Sec
Total Counter :	1446340	Total Running Time :	737 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	99	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.78	kN	No		
HEP :	25.0 %	24.79	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	20.33	kN	Yes 15	Times	
Ref :		19.83	kN			
LCP :	2.5 %	19.34	kN	Yes 15	Times	
LEP :	25.0 %	14.88	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	13.88	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.03	kN	Min :	2.80	kN	Punch NO.;	16
SD :	4.40	%	Max :	3.43	kN	Punch NO.;	8
Mean Main Pressure :	19.97	kN	Min :	18.67	kN	Punch NO.;	16
SD :	2.90	%	Max :	21.48	kN	Punch NO.;	8
Filling Depth :	Increase ;	832	Times	Decrease ;	780	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	17	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.69	mm	Pre Thickness ;	1.70	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.85	mm	Main Thickness ;	0.86	mm
Filling Depth :	6.58	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	1446340	Tablets			
A.W.C Counter :	1426007	Tablets			
HEP :	1171 (0.1%)	Tablets	LEP :	558 (0.0%)	Tablets
GOOD :	1424278 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	gp98929	Batch NO. :	AIM2500220
Print Interval :	50000 Tablets	Running Time :	13 Hour 07 Min 36 Sec
Total Counter :	1446340	Total Running Time :	737 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	95	%	Manual ;	32	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.90	kN	No		
HEP :	25.0 %	22.98	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	18.84	kN	Yes 15	Times	
Ref :		18.39	kN			
LCP :	2.5 %	17.93	kN	Yes 15	Times	
LEP :	25.0 %	13.79	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.87	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.71	kN	Min :	2.44	kN	Punch NO.;	18
SD :	4.20	%	Max :	3.00	kN	Punch NO.;	44
Mean Main Pressure :	17.90	kN	Min :	16.90	kN	Punch NO.;	18
SD :	2.70	%	Max :	19.00	kN	Punch NO.;	44
Filling Depth :	Increase ;	570	Times	Decrease ;	549	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.97	mm	Main Thickness ;	0.98	mm
Filling Depth :	6.85	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.800	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	1	Min			
Lower Punch Remain Time (S2):	21	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.03	kN		
	Max ;	0.07	kN	Max Punch ;	4
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	17
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.07	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	1446340	Tablets			
A.W.C Counter :	1426007	Tablets			
HEP :	1171 (0.1%)	Tablets	LEP :	558 (0.0%)	Tablets
GOOD :	1424278 (99.9%)	Tablets			