

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	pn98247	Batch NO. :	AIM2500320
Print Interval :	50000 Tablets	Running Time :	08 Hour 06 Min 27 Sec
Total Counter :	906706	Total Running Time :	745 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	92	%	Manual ;	20	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.41	kN	No		
HEP :	25.0 %	19.62	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	16.09	kN	Yes 15	Times	
Ref :		15.70	kN			
LCP :	2.5 %	15.31	kN	Yes 15	Times	
LEP :	25.0 %	11.77	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.99	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.92	kN	Min :	2.74	kN	Punch NO.;	22
SD :	4.60	%	Max :	3.32	kN	Punch NO.;	42
Mean Main Pressure :	15.71	kN	Min :	14.79	kN	Punch NO.;	4
SD :	3.40	%	Max :	17.16	kN	Punch NO.;	44
Filling Depth :	Increase ; 300	Times	Decrease ;	295	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.69	mm	Pre Thickness ;	1.70	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	3.99	mm	Main Thickness ;	1.00	mm
Filling Depth :	5.60	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.816	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	50
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	1
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	906706	Tablets			
A.W.C Counter :	892713	Tablets			
HEP :	159 (0.0%)	Tablets	LEP :	61 (0.0%)	Tablets
GOOD :	892493 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Amioda 200mgSTAl3A00
User ID :	pn98247	Batch NO. :	AIM2500320
Print Interval :	50000 Tablets	Running Time :	08 Hour 06 Min 27 Sec
Total Counter :	906706	Total Running Time :	745 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	95	%	Manual ;	32	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		1500000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		25	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.93	kN	No		
HEP :	25.0 %	18.20	kN	Yes 10	Rotations 15	Tablets
HCP :	2.5 %	14.93	kN	Yes 15	Times	
Ref :		14.56	kN			
LCP :	2.5 %	14.20	kN	Yes 15	Times	
LEP :	25.0 %	10.92	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.19	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.59	kN	Min :	2.32	kN	Punch NO.;	30
SD :	6.00	%	Max :	3.13	kN	Punch NO.;	6
Mean Main Pressure :	14.00	kN	Min :	13.15	kN	Punch NO.;	27
SD :	3.30	%	Max :	15.36	kN	Punch NO.;	6
Filling Depth :	Increase ;	496	Times	Decrease ;	490	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	4.70	mm	Pre Thickness ;	1.71	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.14	mm	Main Thickness ;	1.15	mm
Filling Depth :	5.78	mm	Current Cam :	Cam B	
Main Air pressure :	0.816	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	2	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.05	kN	Max Punch ;	50
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.17	kN	Max Punch ;	1
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	906706	Tablets			
A.W.C Counter :	892713	Tablets			
HEP :	159 (0.0%)	Tablets	LEP :	61 (0.0%)	Tablets
GOOD :	892493 (100.0%)	Tablets			