

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	01 Hour 57 Min 04 Sec
Total Counter :	209480	Total Running Time :	752 Hour 35 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	260	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.33	kN	No		
HEP :	25.0 %	30.12	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	24.58	kN	Yes	15	Times
Ref :		24.10	kN			
LCP :	2.0 %	23.62	kN	Yes	15	Times
LEP :	25.0 %	18.07	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	16.87	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	4.02	kN	Min :	3.63	kN	Punch NO.;	19
SD :	4.70	%	Max :	4.47	kN	Punch NO.;	46
Mean Main Pressure :	24.14	kN	Min :	22.02	kN	Punch NO.;	19
SD :	4.30	%	Max :	26.63	kN	Punch NO.;	46
Filling Depth :	Increase ;	126	Times	Decrease ;	115	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	47	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	3.48	mm
Filling Depth :	9.96	mm	Current Cam :	Cam C	
Main Air pressure :	0.784	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	53
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.25	kN	Max Punch ;	49
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	209480	Tablets			
A.W.C Counter :	199061	Tablets			
HEP :	183 (0.1%)	Tablets	LEP :	275 (0.1%)	Tablets
GOOD :	198603 (99.8%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	01 Hour 57 Min 04 Sec
Total Counter :	209480	Total Running Time :	752 Hour 35 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	260	%	Manual ;	32	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1350000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.01	kN	No		
HEP :	25.0 %	30.78	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	25.11	kN	Yes	15	Times
Ref :		24.62	kN			
LCP :	2.0 %	24.13	kN	Yes	15	Times
LEP :	25.0 %	18.47	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	17.24	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.06	kN	Min :	3.68	kN	Punch NO.;	52
SD :	5.60	%	Max :	4.68	kN	Punch NO.;	7
Mean Main Pressure :	24.57	kN	Min :	22.64	kN	Punch NO.;	42
SD :	4.60	%	Max :	27.08	kN	Punch NO.;	46
Filling Depth :	Increase ;	73	Times	Decrease ;	60	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	47	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	10.44	mm	Current Cam :	Cam C	
Main Air pressure :	0.784	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	23	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.04	kN	Max Punch ;	53
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.25	kN	Max Punch ;	49
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.07	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	209480	Tablets			
A.W.C Counter :	199061	Tablets			
HEP :	183 (0.1%)	Tablets	LEP :	275 (0.1%)	Tablets
GOOD :	198603 (99.8%)	Tablets			