

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	06 Hour 50 Min 39 Sec
Total Counter :	759642	Total Running Time :	757 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	272	%	Manual ;	20	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1350000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.29	kN	No		
HEP :	25.0 %	31.04	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	25.33	kN	Yes 15	Times	
Ref :		24.83	kN			
LCP :	2.0 %	24.34	kN	Yes 15	Times	
LEP :	25.0 %	18.63	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.38	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.87	kN	Min :	3.21	kN	Punch NO.;	43
SD :	8.60	%	Max :	4.72	kN	Punch NO.;	18
Mean Main Pressure :	22.90	kN	Min :	19.55	kN	Punch NO.;	43
SD :	6.60	%	Max :	26.59	kN	Punch NO.;	18
Filling Depth :	Increase ;	581	Times	Decrease ;	410	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	46	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	3.48	mm
Filling Depth :	13.56	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.08	kN	Max Punch ;	23
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.09	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	759642	Tablets			
A.W.C Counter :	746956	Tablets			
HEP :	710 (0.1%)	Tablets	LEP :	365 (0.0%)	Tablets
GOOD :	745881 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	06 Hour 50 Min 39 Sec
Total Counter :	759642	Total Running Time :	757 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	274	%	Manual ;	32	RPM
Filling Cam :		Cam D 12.5- 18mm		Cam Range :	Min :	10.50 mm
Target Quantity :		1350000	Tablets		Max :	16.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.72	kN	No		
HEP :	25.0 %	30.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	24.89	kN	Yes 15	Times	
Ref :		24.40	kN			
LCP :	2.0 %	23.91	kN	Yes 15	Times	
LEP :	25.0 %	18.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.08	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.91	kN	Min :	3.36	kN	Punch NO.;	19
SD :	8.60	%	Max :	4.71	kN	Punch NO.;	18
Mean Main Pressure :	24.01	kN	Min :	21.40	kN	Punch NO.;	19
SD :	5.50	%	Max :	27.04	kN	Punch NO.;	45
Filling Depth :	Increase ;	414	Times	Decrease ;	250	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	47	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	13.93	mm	Current Cam :	Cam D 12.5- 18mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.07	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.08	kN	Max Punch ;	23
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.09	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	759642	Tablets			
A.W.C Counter :	746956	Tablets			
HEP :	710 (0.1%)	Tablets	LEP :	365 (0.0%)	Tablets
GOOD :	745881 (99.9%)	Tablets			