

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	08 Hour 14 Min 38 Sec
Total Counter :	909712	Total Running Time :	758 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	272	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	32.29	kN	No		
HEP :	25.0 %	31.04	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	25.33	kN	Yes 15	Times	
Ref :		24.83	kN			
LCP :	2.0 %	24.34	kN	Yes 15	Times	
LEP :	25.0 %	18.63	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.38	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.98	kN	Min :	3.58	kN	Punch NO.;	49
SD :	5.20	%	Max :	4.44	kN	Punch NO.;	7
Mean Main Pressure :	24.87	kN	Min :	22.16	kN	Punch NO.;	49
SD :	4.80	%	Max :	26.98	kN	Punch NO.;	7
Filling Depth :	Increase ;	669	Times	Decrease ;	577	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	46	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	3.48	mm
Filling Depth :	9.99	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.06	kN	Max Punch ;	53
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.39	kN	Max Punch ;	47
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	909712	Tablets			
A.W.C Counter :	896965	Tablets			
HEP :	725 (0.1%)	Tablets	LEP :	365 (0.0%)	Tablets
GOOD :	895875 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	rp98927	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	08 Hour 14 Min 38 Sec
Total Counter :	909712	Total Running Time :	758 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	274	%	Manual ;	32	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		1350000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.72	kN	No		
HEP :	25.0 %	30.50	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	24.89	kN	Yes 15	Times	
Ref :		24.40	kN			
LCP :	2.0 %	23.91	kN	Yes 15	Times	
LEP :	25.0 %	18.30	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	17.08	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.64	kN	Min :	3.37	kN	Punch NO.;	49
SD :	5.30	%	Max :	4.08	kN	Punch NO.;	7
Mean Main Pressure :	24.28	kN	Min :	22.51	kN	Punch NO.;	42
SD :	4.50	%	Max :	26.57	kN	Punch NO.;	14
Filling Depth :	Increase ;	450	Times	Decrease ;	366	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	47	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	10.29	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.795	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.06	kN	Max Punch ;	53
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.39	kN	Max Punch ;	47
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.14	kN	Max Punch ;	17

Tablet Data (N/A)

Total Counter :	909712	Tablets			
A.W.C Counter :	896965	Tablets			
HEP :	725 (0.1%)	Tablets	LEP :	365 (0.0%)	Tablets
GOOD :	895875 (99.9%)	Tablets			