

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	pm98770	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	12 Hour 14 Min 50 Sec
Total Counter :	1339592	Total Running Time :	762 Hour 54 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	285	%	Manual ;	20	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	34.69	kN	No		
HEP :	25.0 %	33.35	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	27.21	kN	Yes 15	Times	
Ref :		26.68	kN			
LCP :	2.0 %	26.15	kN	Yes 15	Times	
LEP :	25.0 %	20.01	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.68	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	3.19	kN	Min :	2.89	kN	Punch NO.;	49
SD :	6.10	%	Max :	3.76	kN	Punch NO.;	22
Mean Main Pressure :	21.23	kN	Min :	18.73	kN	Punch NO.;	49
SD :	6.10	%	Max :	24.59	kN	Punch NO.;	1
Filling Depth :	Increase ;	793	Times	Decrease ;	704	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	48	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.48	mm	Main Thickness ;	3.48	mm
Filling Depth :	10.29	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.807	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	23
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.34	kN	Max Punch ;	42
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.15	kN	Max Punch ;	3

Tablet Data (N/A)

Total Counter :	1339592	Tablets			
A.W.C Counter :	1326337	Tablets			
HEP :	728 (0.1%)	Tablets	LEP :	377 (0.0%)	Tablets
GOOD :	1325232 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBU 600MG STIU2C00
User ID :	pm98770	Batch NO. :	IUM2500560
Print Interval :	50000 Tablets	Running Time :	12 Hour 14 Min 50 Sec
Total Counter :	1339592	Total Running Time :	762 Hour 54 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	284	%	Manual ;	32	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		1350000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	33.86	kN	No		
HEP :	25.0 %	32.56	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	26.57	kN	Yes 15	Times	
Ref :		26.05	kN			
LCP :	2.0 %	25.53	kN	Yes 15	Times	
LEP :	25.0 %	19.54	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	18.23	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	3.02	kN	Min :	2.85	kN	Punch NO.;	42
		3.40	%	Max :	3.24	kN	Punch NO.;	49
Mean Main Pressure :		21.87	kN	Min :	20.24	kN	Punch NO.;	42
	SD :	3.80	%	Max :	23.69	kN	Punch NO.;	1
Filling Depth :	Increase ;	613	Times	Decrease ;	470	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	48	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.50	mm	Pre Thickness ;	4.50	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.50	mm	Main Thickness ;	3.50	mm
Filling Depth :	10.54	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.807	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.01	kN		
	Max ;	0.05	kN	Max Punch ;	23
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.34	kN	Max Punch ;	42
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.16	kN	Max Punch ;	3

Tablet Data (N/A)

Total Counter :	1339592	Tablets			
A.W.C Counter :	1326337	Tablets			
HEP :	728 (0.1%)	Tablets	LEP :	377 (0.0%)	Tablets
GOOD :	1325232 (99.9%)	Tablets			