

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	yd98913	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	01 Hour 45 Min 05 Sec
Total Counter :	450336	Total Running Time :	764 Hour 45 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		6000000	Tablets			
Oil Lubrication :		0.000	MPa			
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.12	kN	No		
HEP :	25.0 %	18.39	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	15.00	kN	Yes	15	Times
Ref :		14.71	kN			
LCP :	2.0 %	14.42	kN	Yes	15	Times
LEP :	25.0 %	11.03	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.30	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.13	kN	Min :	1.05	kN	Punch NO.;	14
SD :	2.90	%	Max :	1.20	kN	Punch NO.;	2
Mean Main Pressure :	14.84	kN	Min :	13.46	kN	Punch NO.;	19
SD :	4.50	%	Max :	16.22	kN	Punch NO.;	75
Filling Depth :	Increase ;	30	Times	Decrease ;	48	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.40	mm	Main Thickness ;	1.41	mm
Filling Depth :	5.94	mm	Current Cam :	Cam B	
Main Air pressure :	0.813	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.21	kN	Max Punch ;	44
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	17
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.13	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	450336	Tablets			
A.W.C Counter :	444197	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	444163 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	yd98913	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	01 Hour 45 Min 05 Sec
Total Counter :	450336	Total Running Time :	764 Hour 45 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		6000000	Tablets			
Oil Lubrication :		0.000	MPa			
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		10	Min	Supply Time ;	0.5	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.59	kN	No		
HEP :	25.0 %	15.96	kN	Yes	10	Rotations
HCP :	2.0 %	13.02	kN	Yes	15	Times
Ref :		12.76	kN			
LCP :	2.0 %	12.51	kN	Yes	15	Times
LEP :	25.0 %	9.57	kN	Yes	10	Rotations
LSP :	30.0 %	8.94	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.23	kN	Min :	1.19	kN	Punch NO.;	12
SD :	1.80	%	Max :	1.30	kN	Punch NO.;	44
Mean Main Pressure :	12.60	kN	Min :	11.51	kN	Punch NO.;	50
SD :	3.00	%	Max :	13.59	kN	Punch NO.;	60
Filling Depth :	Increase ;	66	Times	Decrease ;	59	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	5.66	mm	Current Cam :	Cam B	
Main Air pressure :	0.813	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	19	Min			
Lower Punch Remain Time (S2):	2	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.21	kN	Max Punch ;	44
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	17
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.13	kN	Max Punch ;	37

Tablet Data (N/A)

Total Counter :	450336	Tablets			
A.W.C Counter :	444197	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	33 (0.0%)	Tablets
GOOD :	444163 (100.0%)	Tablets			