

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	pn98247	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	04 Hour 27 Min 36 Sec
Total Counter :	1150720	Total Running Time :	767 Hour 27 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.71	kN	No		
HEP :	25.0 %	17.99	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.68	kN	Yes 15	Times	
Ref :		14.39	kN			
LCP :	2.0 %	14.10	kN	Yes 15	Times	
LEP :	25.0 %	10.79	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	10.07	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	1.08	kN	Min :	1.02	kN	Punch NO.;	14
		2.70	%	Max :	1.15	kN	Punch NO.;	3
Mean Main Pressure :		14.22	kN	Min :	13.12	kN	Punch NO.;	14
	SD :	4.20	%	Max :	15.95	kN	Punch NO.;	76
Filling Depth :	Increase ;	209	Times	Decrease ;	238	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.48	mm
Filling Depth :	5.96	mm	Current Cam :	Cam B	
Main Air pressure :	0.759	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	16
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	17
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.15	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	1150720	Tablets			
A.W.C Counter :	1142646	Tablets			
HEP :	4 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	1142607 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	pn98247	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	04 Hour 27 Min 36 Sec
Total Counter :	1150720	Total Running Time :	767 Hour 27 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		5	Min	Supply Time ;	4.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.04	kN	No		
HEP :	25.0 %	16.38	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.37	kN	Yes 15	Times	
Ref :		13.11	kN			
LCP :	2.0 %	12.84	kN	Yes 15	Times	
LEP :	25.0 %	9.83	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.17	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.25	kN	Min :	1.18	kN	Punch NO.;	25
SD :	2.00	%	Max :	1.31	kN	Punch NO.;	77
Mean Main Pressure :	13.21	kN	Min :	12.36	kN	Punch NO.;	26
SD :	3.30	%	Max :	14.03	kN	Punch NO.;	41
Filling Depth :	Increase ;	122	Times	Decrease ;	111	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	1.55	mm
Filling Depth :	5.93	mm	Current Cam :	Cam B	
Main Air pressure :	0.759	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.14	kN	Max Punch ;	16
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	17
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	33

Tablet Data (N/A)

Total Counter :	1150720	Tablets			
A.W.C Counter :	1142646	Tablets			
HEP :	4 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	1142607 (100.0%)	Tablets			