

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	ka98463	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	11 Hour 59 Min 57 Sec
Total Counter :	3101902	Total Running Time :	775 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		180	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.05	kN	No		
HEP :	25.0 %	16.39	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.38	kN	Yes 15	Times	
Ref :		13.11	kN			
LCP :	2.0 %	12.85	kN	Yes 15	Times	
LEP :	25.0 %	9.84	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.18	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.02	kN	Min :	0.95	kN	Punch NO.;	14
SD :	3.30	%	Max :	1.13	kN	Punch NO.;	35
Mean Main Pressure :	13.05	kN	Min :	11.56	kN	Punch NO.;	22
SD :	5.50	%	Max :	15.35	kN	Punch NO.;	75
Filling Depth :	Increase ;	864	Times	Decrease ;	889	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	1.55	mm
Filling Depth :	5.96	mm	Current Cam :	Cam B	
Main Air pressure :	0.746	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	108	Min			
Lower Punch Remain Time (S2):	84	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	16
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	51
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	9

Tablet Data (N/A)

Total Counter :	3101902	Tablets			
A.W.C Counter :	3093475	Tablets			
HEP :	24 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	3093416	Tablets			
	(100.0%)				

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	ka98463	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	11 Hour 59 Min 57 Sec
Total Counter :	3101902	Total Running Time :	775 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		180	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.87	kN	No		
HEP :	25.0 %	17.18	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	14.02	kN	Yes 15	Times	
Ref :		13.74	kN			
LCP :	2.0 %	13.47	kN	Yes 15	Times	
LEP :	25.0 %	10.31	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.62	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.18	kN	Min :	1.14	kN	Punch NO.;	6
SD :	1.80	%	Max :	1.25	kN	Punch NO.;	77
Mean Main Pressure :	13.59	kN	Min :	12.40	kN	Punch NO.;	50
SD :	3.20	%	Max :	14.69	kN	Punch NO.;	77
Filling Depth :	Increase ;	221	Times	Decrease ;	219	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	1.55	mm
Filling Depth :	5.87	mm	Current Cam :	Cam B	
Main Air pressure :	0.746	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	108	Min			
Lower Punch Remain Time (S2):	84	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.19	kN	Max Punch ;	16
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.11	kN	Max Punch ;	51
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.13	kN	Max Punch ;	48

Tablet Data (N/A)

Total Counter :	3101902	Tablets			
A.W.C Counter :	3093475	Tablets			
HEP :	24 (0.0%)	Tablets	LEP :	35 (0.0%)	Tablets
GOOD :	3093416 (100.0%)	Tablets			