

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	yd98913	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	18 Hour 22 Min 45 Sec
Total Counter :	4753486	Total Running Time :	781 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		6000000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		180	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.33	kN	No		
HEP :	25.0 %	16.66	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	13.59	kN	Yes 15	Times	
Ref :		13.33	kN			
LCP :	2.0 %	13.06	kN	Yes 15	Times	
LEP :	25.0 %	10.00	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	9.33	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.06	kN	Min :	0.99	kN	Punch NO.;	77
SD :	2.60	%	Max :	1.17	kN	Punch NO.;	75
Mean Main Pressure :	13.27	kN	Min :	11.59	kN	Punch NO.;	77
SD :	4.80	%	Max :	15.29	kN	Punch NO.;	75
Filling Depth :	Increase ;	1462	Times	Decrease ;	1490	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	1.55	mm
Filling Depth :	5.92	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	128	Min			
Lower Punch Remain Time (S2):	64	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	8
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.12	kN	Max Punch ;	71
Ejection Force :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	4753486	Tablets			
A.W.C Counter :	4744288	Tablets			
HEP :	437 (0.0%)	Tablets	LEP :	37 (0.0%)	Tablets
GOOD :	4743814 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	SETRA50MG STSH4A00
User ID :	yd98913	Batch NO. :	SHM2500450
Print Interval :	50000 Tablets	Running Time :	18 Hour 22 Min 45 Sec
Total Counter :	4753486	Total Running Time :	781 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	18	%	Manual ;	12	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		6000000	Tablets			
Oil Lubrication :		0.400	MPa			
Upper Punch Interval Time(S1) ;		200	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		180	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		1.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.23	kN	No		
HEP :	25.0 %	18.49	kN	Yes	10	Rotations 15 Tablets
HCP :	2.0 %	15.09	kN	Yes	15	Times
Ref :		14.79	kN			
LCP :	2.0 %	14.50	kN	Yes	15	Times
LEP :	25.0 %	11.10	kN	Yes	10	Rotations 15 Tablets
LSP :	30.0 %	10.36	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.28	kN	Min :	1.23	kN	Punch NO.;	22
SD :	2.00	%	Max :	1.41	kN	Punch NO.;	18
Mean Main Pressure :	14.71	kN	Min :	13.31	kN	Punch NO.;	50
SD :	3.60	%	Max :	16.97	kN	Punch NO.;	18
Filling Depth :	Increase ;	411	Times	Decrease ;	413	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	5	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	2.61	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.54	mm	Main Thickness ;	1.55	mm
Filling Depth :	6.03	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	128	Min			
Lower Punch Remain Time (S2):	64	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.15	kN	Max Punch ;	5
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.12	kN	Max Punch ;	71
Ejection Force :	Average ;	0.11	kN		
	Max ;	0.15	kN	Max Punch ;	44

Tablet Data (N/A)

Total Counter :	4753486	Tablets			
A.W.C Counter :	4744288	Tablets			
HEP :	437 (0.0%)	Tablets	LEP :	37 (0.0%)	Tablets
GOOD :	4743814 (100.0%)	Tablets			