

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPR 400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500240
Print Interval :	50000 Tablets	Running Time :	04 Hour 55 Min 40 Sec
Total Counter :	750316	Total Running Time :	790 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	12	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		2.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.94	kN	No		
HEP :	25.0 %	21.09	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	17.21	kN	Yes 15	Times	
Ref :		16.87	kN			
LCP :	2.0 %	16.54	kN	Yes 15	Times	
LEP :	25.0 %	12.66	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.81	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1 Rotations			Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.38	kN	Min :	1.32	kN	Punch NO.;	15
SD :	4.40	%	Max :	1.73	kN	Punch NO.;	36
Mean Main Pressure :	16.75	kN	Min :	15.18	kN	Punch NO.;	4
SD :	4.10	%	Max :	18.89	kN	Punch NO.;	22
Filling Depth :	Increase ; 551	Times	Decrease ;	494	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.50	mm
Filling Depth :	8.80	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.760	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.45	kN		
	Max ;	0.51	kN	Max Punch ;	35
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.70	kN	Max Punch ;	36
Ejection Force :	Average ;	0.15	kN		
	Max ;	0.93	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	750316	Tablets			
A.W.C Counter :	738685	Tablets			
HEP :	166 (0.0%)	Tablets	LEP :	397 (0.1%)	Tablets
GOOD :	738122 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPR 400MG STIU2B00
User ID :	pb97604	Batch NO. :	IUM2500240
Print Interval :	50000 Tablets	Running Time :	04 Hour 55 Min 40 Sec
Total Counter :	750316	Total Running Time :	790 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	12	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		2.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.78	kN	No		
HEP :	25.0 %	20.94	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	17.09	kN	Yes 15	Times	
Ref :		16.75	kN			
LCP :	2.0 %	16.42	kN	Yes 15	Times	
LEP :	25.0 %	12.56	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	11.73	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.10	kN	Min :	1.04	kN	Punch NO.;	9
SD :	7.50	%	Max :	1.56	kN	Punch NO.;	36
Mean Main Pressure :	16.62	kN	Min :	15.09	kN	Punch NO.;	47
SD :	4.60	%	Max :	18.08	kN	Punch NO.;	14
Filling Depth :	Increase ;	430	Times	Decrease ;	362	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	22	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.65	mm	Main Thickness ;	1.65	mm
Filling Depth :	9.12	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.760	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	16	Min			
Lower Punch Remain Time (S2):	36	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.45	kN		
	Max ;	0.53	kN	Max Punch ;	35
Lower Punch :	Average ;	0.17	kN		
	Max ;	0.70	kN	Max Punch ;	36
Ejection Force :	Average ;	0.15	kN		
	Max ;	0.93	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	750316	Tablets			
A.W.C Counter :	738685	Tablets			
HEP :	166 (0.0%)	Tablets	LEP :	397 (0.1%)	Tablets
GOOD :	738122 (99.9%)	Tablets			