

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPR 400MG STIU2B00
User ID :	pm98770	Batch NO. :	IUM2500240
Print Interval :	50000 Tablets	Running Time :	07 Hour 39 Min 51 Sec
Total Counter :	1150484	Total Running Time :	793 Hour 37 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	12	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.29	kN	No		
HEP :	25.0 %	22.40	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	18.28	kN	Yes 15	Times	
Ref :		17.92	kN			
LCP :	2.0 %	17.56	kN	Yes 15	Times	
LEP :	25.0 %	13.44	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.54	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.51	kN	Min :	1.45	kN	Punch NO.;	30
SD :	3.40	%	Max :	1.77	kN	Punch NO.;	36
Mean Main Pressure :	17.91	kN	Min :	15.91	kN	Punch NO.;	30
SD :	4.40	%	Max :	19.78	kN	Punch NO.;	22
Filling Depth :	Increase ;	714	Times	Decrease ;	654	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.50	mm
Filling Depth :	8.77	mm	Current Cam :	Cam C	
Main Air pressure :	0.766	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.29	kN		
	Max ;	0.37	kN	Max Punch ;	19
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.45	kN	Max Punch ;	36
Ejection Force :	Average ;	0.18	kN		
	Max ;	0.87	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	1150484	Tablets			
A.W.C Counter :	1134551	Tablets			
HEP :	298 (0.0%)	Tablets	LEP :	397 (0.0%)	Tablets
GOOD :	1133856 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPR 400MG STIU2B00
User ID :	pm98770	Batch NO. :	IUM2500240
Print Interval :	50000 Tablets	Running Time :	07 Hour 39 Min 51 Sec
Total Counter :	1150484	Total Running Time :	793 Hour 37 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	12	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.61	kN	No		
HEP :	25.0 %	21.74	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	17.74	kN	Yes 15	Times	
Ref :		17.39	kN			
LCP :	2.0 %	17.04	kN	Yes 15	Times	
LEP :	25.0 %	13.04	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.17	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.32	kN	Min :	1.27	kN	Punch NO.;	33
SD :	4.70	%	Max :	1.64	kN	Punch NO.;	36
Mean Main Pressure :	17.83	kN	Min :	16.26	kN	Punch NO.;	32
SD :	4.50	%	Max :	20.12	kN	Punch NO.;	29
Filling Depth :	Increase ;	614	Times	Decrease ;	548	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.65	mm	Main Thickness ;	1.65	mm
Filling Depth :	8.79	mm	Current Cam :	Cam C	
Main Air pressure :	0.766	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	35	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.37	kN	Max Punch ;	16
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.45	kN	Max Punch ;	36
Ejection Force :	Average ;	0.18	kN		
	Max ;	0.87	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	1150484	Tablets			
A.W.C Counter :	1134551	Tablets			
HEP :	298 (0.0%)	Tablets	LEP :	397 (0.0%)	Tablets
GOOD :	1133856 (99.9%)	Tablets			