

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPR 400MG STIU2B00
User ID :	rp98927	Batch NO. :	IUM2500240
Print Interval :	50000 Tablets	Running Time :	14 Hour 18 Min 18 Sec
Total Counter :	1993008	Total Running Time :	800 Hour 16 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	12	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	23.29	kN	No		
HEP :	25.0 %	22.40	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	18.28	kN	Yes 15	Times	
Ref :		17.92	kN			
LCP :	2.0 %	17.56	kN	Yes 15	Times	
LEP :	25.0 %	13.44	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.54	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.65	kN	Min :	1.61	kN	Punch NO.;	1
SD :	2.00	%	Max :	1.81	kN	Punch NO.;	29
Mean Main Pressure :	17.93	kN	Min :	16.51	kN	Punch NO.;	4
SD :	4.00	%	Max :	19.46	kN	Punch NO.;	22
Filling Depth :	Increase ;	1294	Times	Decrease ;	1195	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.50	mm
Filling Depth :	8.59	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.742	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	60	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.41	kN	Max Punch ;	43
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.73	kN	Max Punch ;	29
Ejection Force :	Average ;	0.15	kN		
	Max ;	0.43	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1993008	Tablets			
A.W.C Counter :	1975844	Tablets			
HEP :	1134 (0.1%)	Tablets	LEP :	397 (0.0%)	Tablets
GOOD :	1974313 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPR 400MG STIU2B00
User ID :	rp98927	Batch NO. :	IUM2500240
Print Interval :	50000 Tablets	Running Time :	14 Hour 18 Min 18 Sec
Total Counter :	1993008	Total Running Time :	800 Hour 16 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	90	%	Manual ;	12	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2025000	Tablets			
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	1.0	Sec
Lower Punch Interval Time(S2) ;		40	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	22.80	kN	No		
HEP :	25.0 %	21.93	kN	Yes 10	Rotations 15	Tablets
HCP :	2.0 %	17.89	kN	Yes 15	Times	
Ref :		17.54	kN			
LCP :	2.0 %	17.19	kN	Yes 15	Times	
LEP :	25.0 %	13.16	kN	Yes 10	Rotations 15	Tablets
LSP :	30.0 %	12.28	kN	No		
SD limit :	20.0 %			Yes		
Pre HSP		20.00	kN	Yes		
Mean Calculation range :	1	Rotations		Calculation Pass :	1	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.64	kN	Min :	1.60	kN	Punch NO.;	3
SD :	2.10	%	Max :	1.79	kN	Punch NO.;	29
Mean Main Pressure :	16.09	kN	Min :	14.79	kN	Punch NO.;	32
SD :	3.40	%	Max :	17.55	kN	Punch NO.;	29
Filling Depth :	Increase ;	1175	Times	Decrease ;	1013	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	5.20	mm	Pre Thickness ;	2.20	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.65	mm	Main Thickness ;	1.65	mm
Filling Depth :	9.44	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.742	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	60	Min			
Lower Punch Remain Time (S2):	40	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	On		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.45	kN	Max Punch ;	43
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.73	kN	Max Punch ;	29
Ejection Force :	Average ;	0.15	kN		
	Max ;	0.43	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1993008	Tablets			
A.W.C Counter :	1975844	Tablets			
HEP :	1134 (0.1%)	Tablets	LEP :	397 (0.0%)	Tablets
GOOD :	1974313 (99.9%)	Tablets			