

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	sj97904	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	01 Hour 10 Min 00 Sec
Total Counter :	300238	Total Running Time :	801 Hour 26 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.33	kN	No		
HEP :	25.0 %	17.62	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.38	kN	Yes 10	Times	
Ref :		14.10	kN			
LCP :	2.0 %	13.82	kN	Yes 10	Times	
LEP :	25.0 %	10.57	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.53	kN	Min :	2.41	kN	Punch NO.;	1
		2.00	%	Max :	2.64	kN	Punch NO.;	6
Mean Main Pressure :		14.00	kN	Min :	13.16	kN	Punch NO.;	1
	SD :	2.60	%	Max :	14.96	kN	Punch NO.;	70
Filling Depth :	Increase ;	20	Times	Decrease ;	21	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.37	mm	Main Thickness ;	1.87	mm
Filling Depth :	7.76	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	53	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.46	kN	Max Punch ;	24
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.31	kN	Max Punch ;	57
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	300238	Tablets			
A.W.C Counter :	293856	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	293855	Tablets			
	(100.0%)				

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	sj97904	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	01 Hour 10 Min 00 Sec
Total Counter :	300238	Total Running Time :	801 Hour 26 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.31	kN	No		
HEP :	25.0 %	19.53	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.94	kN	Yes 10	Times	
Ref :		15.63	kN			
LCP :	2.0 %	15.31	kN	Yes 10	Times	
LEP :	25.0 %	11.72	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.94	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.61	kN	Min :	2.45	kN	Punch NO.;	49
SD :	2.10	%	Max :	2.75	kN	Punch NO.;	42
Mean Main Pressure :	15.57	kN	Min :	14.87	kN	Punch NO.;	1
SD :	2.30	%	Max :	16.41	kN	Punch NO.;	32
Filling Depth :	Increase ; 26	Times	Decrease ;	40	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.43	mm	Main Thickness ;	1.93	mm
Filling Depth :	7.54	mm	Current Cam :	Cam C	
Main Air pressure :	0.795	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	53	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.47	kN	Max Punch ;	26
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.31	kN	Max Punch ;	57
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.09	kN	Max Punch ;	74

Tablet Data (N/A)

Total Counter :	300238	Tablets			
A.W.C Counter :	293856	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	293855 (100.0%)	Tablets			