

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	sj97904	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	03 Hour 06 Min 19 Sec
Total Counter :	800618	Total Running Time :	803 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.46	kN	No		
HEP :	25.0 %	17.75	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.48	kN	Yes 10	Times	
Ref :		14.20	kN			
LCP :	2.0 %	13.91	kN	Yes 10	Times	
LEP :	25.0 %	10.65	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.94	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.44	kN	Min :	2.33	kN	Punch NO.;	21
		2.00	%	Max :	2.56	kN	Punch NO.;	57
Mean Main Pressure :		14.26	kN	Min :	13.27	kN	Punch NO.;	26
	SD :	2.80	%	Max :	15.13	kN	Punch NO.;	39
Filling Depth :	Increase ;	36	Times	Decrease ;	54	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.41	mm	Main Thickness ;	1.91	mm
Filling Depth :	7.49	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	58	Min			
Lower Punch Remain Time (S2):	58	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.44	kN		
	Max ;	0.56	kN	Max Punch ;	50
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.33	kN	Max Punch ;	58
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.11	kN	Max Punch ;	75

Tablet Data (N/A)

Total Counter :	800618	Tablets			
A.W.C Counter :	793868	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	793867	Tablets			
	(100.0%)				

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	sj97904	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	03 Hour 06 Min 19 Sec
Total Counter :	800618	Total Running Time :	803 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.14	kN	No		
HEP :	25.0 %	19.37	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	15.80	kN	Yes 10	Times	
Ref :		15.49	kN			
LCP :	2.0 %	15.18	kN	Yes 10	Times	
LEP :	25.0 %	11.62	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	10.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.56	kN	Min :	2.45	kN	Punch NO.;	7
		1.80	%	Max :	2.65	kN	Punch NO.;	22
Mean Main Pressure :		15.75	kN	Min :	14.81	kN	Punch NO.;	8
	SD :	2.70	%	Max :	16.92	kN	Punch NO.;	61
Filling Depth :	Increase ;	28	Times	Decrease ;	47	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	3.00	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.47	mm	Main Thickness ;	1.97	mm
Filling Depth :	7.50	mm	Current Cam :	Cam C	
Main Air pressure :	0.794	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	58	Min			
Lower Punch Remain Time (S2):	58	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.44	kN		
	Max ;	0.56	kN	Max Punch ;	50
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.32	kN	Max Punch ;	58
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.10	kN	Max Punch ;	75

Tablet Data (N/A)

Total Counter :	800618	Tablets			
A.W.C Counter :	793868	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	793867	Tablets			
	(100.0%)				