

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	sj97904	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	04 Hour 04 Min 30 Sec
Total Counter :	1050884	Total Running Time :	804 Hour 20 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.50	kN	No		
HEP :	25.0 %	16.82	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.73	kN	Yes 10	Times	
Ref :		13.46	kN			
LCP :	2.0 %	13.19	kN	Yes 10	Times	
LEP :	25.0 %	10.09	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.29	kN	Min :	2.18	kN	Punch NO.;	17
		1.80	%	Max :	2.41	kN	Punch NO.;	48
Mean Main Pressure :		13.50	kN	Min :	12.84	kN	Punch NO.;	1
	SD :	2.50	%	Max :	14.42	kN	Punch NO.;	62
Filling Depth :	Increase ;	49	Times	Decrease ;	54	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	2.00	mm
Filling Depth :	8.03	mm	Current Cam :	Cam C	
Main Air pressure :	0.776	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	80	Min			
Lower Punch Remain Time (S2):	60	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.50	kN	Max Punch ;	58
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.33	kN	Max Punch ;	57
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	75

Tablet Data (N/A)

Total Counter :	1050884	Tablets			
A.W.C Counter :	1044084	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1044083 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	sj97904	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	04 Hour 04 Min 30 Sec
Total Counter :	1050884	Total Running Time :	804 Hour 20 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		80	Min	Supply Time ;	0.3	Sec
Lower Punch Interval Time(S2) ;		60	Min	Supply Time ;	0.3	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.41	kN	No		
HEP :	25.0 %	17.71	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.45	kN	Yes 10	Times	
Ref :		14.17	kN			
LCP :	2.0 %	13.88	kN	Yes 10	Times	
LEP :	25.0 %	10.62	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.92	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.51	kN	Min :	2.34	kN	Punch NO.;	9
		2.30	%	Max :	2.64	kN	Punch NO.;	52
Mean Main Pressure :		14.35	kN	Min :	13.20	kN	Punch NO.;	9
	SD :	3.10	%	Max :	15.24	kN	Punch NO.;	51
Filling Depth :	Increase ;	37	Times	Decrease ;	51	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	2.10	mm
Filling Depth :	7.65	mm	Current Cam :	Cam C	
Main Air pressure :	0.776	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	80	Min			
Lower Punch Remain Time (S2):	60	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.38	kN		
	Max ;	0.50	kN	Max Punch ;	58
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.31	kN	Max Punch ;	57
Ejection Force :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	2

Tablet Data (N/A)

Total Counter :	1050884	Tablets			
A.W.C Counter :	1044084	Tablets			
HEP :	1 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1044083 (100.0%)	Tablets			