

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	ms98171	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	06 Hour 12 Min 17 Sec
Total Counter :	1601182	Total Running Time :	806 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.34	kN	No		
HEP :	25.0 %	15.72	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.82	kN	Yes 10	Times	
Ref :		12.57	kN			
LCP :	2.0 %	12.32	kN	Yes 10	Times	
LEP :	25.0 %	9.43	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.16	kN	Punch NO.;	19
SD :	1.70	%	Max :	2.32	kN	Punch NO.;	64
Mean Main Pressure :	12.61	kN	Min :	11.85	kN	Punch NO.;	19
SD :	2.90	%	Max :	13.43	kN	Punch NO.;	64
Filling Depth :	Increase ; 72	Times	Decrease ; 94	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	2.05	mm
Filling Depth :	7.52	mm	Current Cam :	Cam C	
Main Air pressure :	0.760	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.18	kN	Max Punch ;	24
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.35	kN	Max Punch ;	58
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	1601182	Tablets			
A.W.C Counter :	1592291	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1592281 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	ms98171	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	06 Hour 12 Min 17 Sec
Total Counter :	1601182	Total Running Time :	806 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.96	kN	No		
HEP :	25.0 %	17.27	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.09	kN	Yes 10	Times	
Ref :		13.82	kN			
LCP :	2.0 %	13.54	kN	Yes 10	Times	
LEP :	25.0 %	10.36	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.67	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.27	kN	Min :	2.18	kN	Punch NO.;	8
SD :	1.30	%	Max :	2.38	kN	Punch NO.;	61
Mean Main Pressure :	13.74	kN	Min :	12.70	kN	Punch NO.;	8
SD :	2.60	%	Max :	14.43	kN	Punch NO.;	74
Filling Depth :	Increase ; 43	Times	Decrease ; 58	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.65	mm	Main Thickness ;	2.15	mm
Filling Depth :	7.62	mm	Current Cam :	Cam C	
Main Air pressure :	0.760	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	35	Min			
Lower Punch Remain Time (S2):	26	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.11	kN		
	Max ;	0.16	kN	Max Punch ;	24
Lower Punch :	Average ;	0.16	kN		
	Max ;	0.35	kN	Max Punch ;	58
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	1601182	Tablets			
A.W.C Counter :	1592368	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1592358 (100.0%)	Tablets			