

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	ms98171	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	09 Hour 29 Min 41 Sec
Total Counter :	2451794	Total Running Time :	809 Hour 46 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	26	%	Manual ;	30	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.34	kN	No		
HEP :	25.0 %	15.72	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.82	kN	Yes 10	Times	
Ref :		12.57	kN			
LCP :	2.0 %	12.32	kN	Yes 10	Times	
LEP :	25.0 %	9.43	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.24	kN	Min :	2.17	kN	Punch NO.;	17
		1.60	%	Max :	2.36	kN	Punch NO.;	48
Mean Main Pressure :		12.79	kN	Min :	12.04	kN	Punch NO.;	76
	SD :	3.10	%	Max :	13.92	kN	Punch NO.;	48
Filling Depth :	Increase ;	86	Times	Decrease ;	106	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	2.05	mm
Filling Depth :	7.58	mm	Current Cam :	Cam C	
Main Air pressure :	0.791	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	24
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.34	kN	Max Punch ;	57
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	2451794	Tablets			
A.W.C Counter :	2442910	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2442900 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Sertra 100mgSTSH4B00
User ID :	ms98171	Batch NO. :	SHM2500910
Print Interval :	50000 Tablets	Running Time :	09 Hour 29 Min 41 Sec
Total Counter :	2451794	Total Running Time :	809 Hour 46 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	25	%	Manual ;	48	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		3000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.95	kN	No		
HEP :	25.0 %	16.30	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.30	kN	Yes 10	Times	
Ref :		13.04	kN			
LCP :	2.0 %	12.78	kN	Yes 10	Times	
LEP :	25.0 %	9.78	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.13	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	2.27	kN	Min :	2.20	kN	Punch NO.;	69
		1.50	%	Max :	2.37	kN	Punch NO.;	64
Mean Main Pressure :		12.95	kN	Min :	12.15	kN	Punch NO.;	8
	SD :	2.40	%	Max :	13.87	kN	Punch NO.;	75
Filling Depth :	Increase ;	51	Times	Decrease ;	62	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	258720	Tablets/hour
Feeder : Status ;	Auto		Speed ;	7	RPM
Pre Upper Punch Position ;	2.50	mm			
Pre Lower Punch Position ;	5.60	mm	Pre Thickness ;	3.10	mm
Main Upper Punch Position ;	2.50	mm			
Main Lower Punch Position ;	4.70	mm	Main Thickness ;	2.20	mm
Filling Depth :	7.74	mm	Current Cam :	Cam C	
Main Air pressure :	0.791	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	37	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.06	kN		
	Max ;	0.10	kN	Max Punch ;	71
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.34	kN	Max Punch ;	57
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.08	kN	Max Punch ;	34

Tablet Data (N/A)

Total Counter :	2451794	Tablets			
A.W.C Counter :	2442910	Tablets			
HEP :	10 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	2442900 (100.0%)	Tablets			