

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	01 Hour 36 Min 37 Sec
Total Counter :	201738	Total Running Time :	813 Hour 24 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.34	kN	No		
HEP :	25.0 %	15.72	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	12.82	kN	Yes	10	Times
Ref :		12.57	kN			
LCP :	2.0 %	12.32	kN	Yes	10	Times
LEP :	25.0 %	9.43	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	8.80	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.05	kN	Min :	2.01	kN	Punch NO.;	15
SD :	1.10	%	Max :	2.15	kN	Punch NO.;	23
Mean Main Pressure :	12.75	kN	Min :	11.23	kN	Punch NO.;	26
SD :	5.60	%	Max :	14.95	kN	Punch NO.;	3
Filling Depth :	Increase ;	65	Times	Decrease ;	65	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.51	mm
Filling Depth :	9.28	mm	Current Cam :	Cam C	
Main Air pressure :	0.783	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.29	kN	Max Punch ;	43
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.32	kN	Max Punch ;	23
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.54	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	201738	Tablets			
A.W.C Counter :	197289	Tablets			
HEP :	15 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	197274 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	rp98927	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	01 Hour 36 Min 37 Sec
Total Counter :	201738	Total Running Time :	813 Hour 24 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		40	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	3.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.88	kN	No		
HEP :	25.0 %	20.07	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	16.38	kN	Yes	10 Times	
Ref :		16.06	kN			
LCP :	2.0 %	15.74	kN	Yes	10 Times	
LEP :	25.0 %	12.04	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	11.24	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.84	kN	Min :	1.80	kN	Punch NO.;	28
SD :	1.50	%	Max :	1.99	kN	Punch NO.;	23
Mean Main Pressure :	16.31	kN	Min :	15.03	kN	Punch NO.;	40
SD :	3.40	%	Max :	17.81	kN	Punch NO.;	10
Filling Depth :	Increase ;	39	Times	Decrease ;	31	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.50	mm	Main Thickness ;	1.50	mm
Filling Depth :	9.23	mm	Current Cam :	Cam C	
Main Air pressure :	0.783	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.28	kN	Max Punch ;	43
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.32	kN	Max Punch ;	23
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.54	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	201738	Tablets			
A.W.C Counter :	197289	Tablets			
HEP :	15 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	197274 (100.0%)	Tablets			