

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	07 Hour 04 Min 33 Sec
Total Counter :	894936	Total Running Time :	818 Hour 52 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	80	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.91	kN	No		
HEP :	25.0 %	16.26	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	13.27	kN	Yes	10 Times	
Ref :		13.01	kN			
LCP :	2.0 %	12.75	kN	Yes	10 Times	
LEP :	25.0 %	9.76	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	9.11	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.20	kN	Min :	2.12	kN	Punch NO.;	2
SD :	1.20	%	Max :	2.31	kN	Punch NO.;	48
Mean Main Pressure :	12.87	kN	Min :	11.80	kN	Punch NO.;	27
SD :	3.90	%	Max :	14.17	kN	Punch NO.;	6
Filling Depth :	Increase ;	314	Times	Decrease ;	277	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	16	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.817	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.25	kN	Max Punch ;	43
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.39	kN	Max Punch ;	48
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.46	kN	Max Punch ;	48

Tablet Data (N/A)

Total Counter :	894936	Tablets			
A.W.C Counter :	889550	Tablets			
HEP :	183 (0.0%)	Tablets	LEP :	19 (0.0%)	Tablets
GOOD :	889348 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500413
Print Interval :	50000 Tablets	Running Time :	07 Hour 04 Min 33 Sec
Total Counter :	894936	Total Running Time :	818 Hour 52 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	91	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		3000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.46	kN	No		
HEP :	25.0 %	15.83	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	12.92	kN	Yes	10	Times
Ref :		12.66	kN			
LCP :	2.0 %	12.41	kN	Yes	10	Times
LEP :	25.0 %	9.50	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	8.86	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.12	kN	Min :	2.07	kN	Punch NO.;	3
SD :	1.20	%	Max :	2.23	kN	Punch NO.;	48
Mean Main Pressure :	12.98	kN	Min :	10.46	kN	Punch NO.;	19
SD :	7.80	%	Max :	14.67	kN	Punch NO.;	47
Filling Depth :	Increase ;	131	Times	Decrease ;	119	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	18	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.69	mm	Main Thickness ;	1.70	mm
Filling Depth :	9.40	mm	Current Cam :	Cam C	
Main Air pressure :	0.817	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	10	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.15	kN		
	Max ;	0.25	kN	Max Punch ;	43
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.49	kN	Max Punch ;	48
Ejection Force :	Average ;	0.09	kN		
	Max ;	0.46	kN	Max Punch ;	48

Tablet Data (N/A)

Total Counter :	894936	Tablets			
A.W.C Counter :	889550	Tablets			
HEP :	183 (0.0%)	Tablets	LEP :	19 (0.0%)	Tablets
GOOD :	889348 (100.0%)	Tablets			