

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	09 Hour 12 Min 10 Sec
Total Counter :	1166732	Total Running Time :	836 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	34	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.04	kN	No		
HEP :	25.0 %	17.34	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	14.15	kN	Yes 10	Times	
Ref :		13.87	kN			
LCP :	2.0 %	13.60	kN	Yes 10	Times	
LEP :	25.0 %	10.41	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.71	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.26	kN	Min :	2.20	kN	Punch NO.;	3
SD :	2.70	%	Max :	2.54	kN	Punch NO.;	6
Mean Main Pressure :	14.31	kN	Min :	13.20	kN	Punch NO.;	19
SD :	3.40	%	Max :	15.32	kN	Punch NO.;	44
Filling Depth :	Increase ; 42	Times	Decrease ;	40	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	9.04	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.739	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.18	kN		
	Max ;	0.24	kN	Max Punch ;	16
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.52	kN	Max Punch ;	6
Ejection Force :	Average ;	0.11	kN		
	Max ;	0.96	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1166732	Tablets			
A.W.C Counter :	1161947	Tablets			
HEP :	90 (0.0%)	Tablets	LEP :	3 (0.0%)	Tablets
GOOD :	1161854 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	09 Hour 12 Min 10 Sec
Total Counter :	1166732	Total Running Time :	836 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.55	kN	No		
HEP :	25.0 %	16.88	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	13.77	kN	Yes	10	Times
Ref :		13.50	kN			
LCP :	2.0 %	13.23	kN	Yes	10	Times
LEP :	25.0 %	10.13	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	9.45	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.21	kN	Min :	2.16	kN	Punch NO.;	18
SD :	1.60	%	Max :	2.36	kN	Punch NO.;	8
Mean Main Pressure :	13.63	kN	Min :	11.75	kN	Punch NO.;	19
SD :	6.20	%	Max :	15.35	kN	Punch NO.;	16
Filling Depth :	Increase ;	31	Times	Decrease ;	27	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.03	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.739	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	21	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.19	kN		
	Max ;	0.24	kN	Max Punch ;	41
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.52	kN	Max Punch ;	6
Ejection Force :	Average ;	0.11	kN		
	Max ;	0.96	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1166732	Tablets			
A.W.C Counter :	1161947	Tablets			
HEP :	90 (0.0%)	Tablets	LEP :	3 (0.0%)	Tablets
GOOD :	1161854 (100.0%)	Tablets			