

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	10 Hour 23 Min 07 Sec
Total Counter :	1316774	Total Running Time :	837 Hour 30 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	34	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.76	kN	No		
HEP :	25.0 %	16.11	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.15	kN	Yes 10	Times	
Ref :		12.89	kN			
LCP :	2.0 %	12.63	kN	Yes 10	Times	
LEP :	25.0 %	9.67	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.02	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.18	kN	Punch NO.;	31
SD :	1.80	%	Max :	2.38	kN	Punch NO.;	6
Mean Main Pressure :	13.08	kN	Min :	12.24	kN	Punch NO.;	40
SD :	3.20	%	Max :	13.83	kN	Punch NO.;	28
Filling Depth :	Increase ; 157	Times	Decrease ;	156	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	8.92	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.734	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	43
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.35	kN	Max Punch ;	11
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.54	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1316774	Tablets			
A.W.C Counter :	1310893	Tablets			
HEP :	254 (0.0%)	Tablets	LEP :	10 (0.0%)	Tablets
GOOD :	1310629 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	10 Hour 23 Min 07 Sec
Total Counter :	1316774	Total Running Time :	837 Hour 30 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.55	kN	No		
HEP :	25.0 %	16.88	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	13.77	kN	Yes	10	Times
Ref :		13.50	kN			
LCP :	2.0 %	13.23	kN	Yes	10	Times
LEP :	25.0 %	10.13	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	9.45	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.14	kN	Punch NO.;	17
SD :	1.50	%	Max :	2.30	kN	Punch NO.;	49
Mean Main Pressure :	13.72	kN	Min :	11.99	kN	Punch NO.;	27
SD :	6.30	%	Max :	15.61	kN	Punch NO.;	9
Filling Depth :	Increase ;	111	Times	Decrease ;	114	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.82	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.734	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	16	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.17	kN		
	Max ;	0.25	kN	Max Punch ;	43
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.34	kN	Max Punch ;	11
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.54	kN	Max Punch ;	6

Tablet Data (N/A)

Total Counter :	1316774	Tablets			
A.W.C Counter :	1310893	Tablets			
HEP :	254 (0.0%)	Tablets	LEP :	10 (0.0%)	Tablets
GOOD :	1310629 (100.0%)	Tablets			