

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	11 Hour 34 Min 22 Sec
Total Counter :	1467342	Total Running Time :	838 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	34	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.98	kN	No		
HEP :	25.0 %	17.29	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	14.11	kN	Yes	10 Times	
Ref :		13.83	kN			
LCP :	2.0 %	13.56	kN	Yes	10 Times	
LEP :	25.0 %	10.37	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	9.68	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.31	kN	Min :	2.27	kN	Punch NO.;	15
SD :	2.00	%	Max :	2.52	kN	Punch NO.;	28
Mean Main Pressure :	13.74	kN	Min :	12.66	kN	Punch NO.;	19
SD :	3.30	%	Max :	14.55	kN	Punch NO.;	45
Filling Depth :	Increase ;	104	Times	Decrease ;	113	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	9.08	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.23	kN	Max Punch ;	43
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.39	kN	Max Punch ;	6
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.58	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1467342	Tablets			
A.W.C Counter :	1458702	Tablets			
HEP :	497 (0.0%)	Tablets	LEP :	57 (0.0%)	Tablets
GOOD :	1458148 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	11 Hour 34 Min 22 Sec
Total Counter :	1467342	Total Running Time :	838 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	102	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.55	kN	No		
HEP :	25.0 %	16.88	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	13.77	kN	Yes	10	Times
Ref :		13.50	kN			
LCP :	2.0 %	13.23	kN	Yes	10	Times
LEP :	25.0 %	10.13	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	9.45	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.29	kN	Min :	2.24	kN	Punch NO.;	42
SD :	1.50	%	Max :	2.41	kN	Punch NO.;	6
Mean Main Pressure :	12.87	kN	Min :	10.31	kN	Punch NO.;	19
SD :	7.00	%	Max :	14.68	kN	Punch NO.;	44
Filling Depth :	Increase ;	103	Times	Decrease ;	101	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.94	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.801	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.16	kN		
	Max ;	0.21	kN	Max Punch ;	43
Lower Punch :	Average ;	0.12	kN		
	Max ;	0.39	kN	Max Punch ;	6
Ejection Force :	Average ;	0.10	kN		
	Max ;	0.58	kN	Max Punch ;	28

Tablet Data (N/A)

Total Counter :	1467342	Tablets			
A.W.C Counter :	1458702	Tablets			
HEP :	497 (0.0%)	Tablets	LEP :	57 (0.0%)	Tablets
GOOD :	1458148 (100.0%)	Tablets			