

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	15 Hour 31 Min 06 Sec
Total Counter :	1967510	Total Running Time :	842 Hour 39 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	101	%	Manual ;	34	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.50	kN	No		
HEP :	25.0 %	16.82	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	13.73	kN	Yes 10	Times	
Ref :		13.46	kN			
LCP :	2.0 %	13.19	kN	Yes 10	Times	
LEP :	25.0 %	10.09	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	9.42	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.20	kN	Min :	2.11	kN	Punch NO.;	10
SD :	1.80	%	Max :	2.37	kN	Punch NO.;	8
Mean Main Pressure :	13.25	kN	Min :	12.26	kN	Punch NO.;	27
SD :	4.50	%	Max :	15.64	kN	Punch NO.;	3
Filling Depth :	Increase ; 365	Times	Decrease ;	331	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	9.08	mm	Current Cam :	Cam C	
Main Air pressure :	0.761	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.22	kN	Max Punch ;	4
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.37	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.40	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1967510	Tablets			
A.W.C Counter :	1957672	Tablets			
HEP :	1012 (0.1%)	Tablets	LEP :	342 (0.0%)	Tablets
GOOD :	1956318 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500513
Print Interval :	50000 Tablets	Running Time :	15 Hour 31 Min 06 Sec
Total Counter :	1967510	Total Running Time :	842 Hour 39 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	99	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.43	kN	No		
HEP :	25.0 %	15.80	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.89	kN	Yes	10 Times	
Ref :		12.64	kN			
LCP :	2.0 %	12.39	kN	Yes	10 Times	
LEP :	25.0 %	9.48	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.85	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.16	kN	Min :	2.10	kN	Punch NO.;	15
SD :	1.30	%	Max :	2.30	kN	Punch NO.;	8
Mean Main Pressure :	11.96	kN	Min :	9.80	kN	Punch NO.;	27
SD :	8.90	%	Max :	13.94	kN	Punch NO.;	2
Filling Depth :	Increase ;	475	Times	Decrease ;	457	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	20	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	9.23	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.761	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.14	kN		
	Max ;	0.22	kN	Max Punch ;	4
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.37	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.38	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1967510	Tablets			
A.W.C Counter :	1957672	Tablets			
HEP :	1012 (0.1%)	Tablets	LEP :	342 (0.0%)	Tablets
GOOD :	1956318 (99.9%)	Tablets			