

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	01 Hour 58 Min 15 Sec
Total Counter :	250056	Total Running Time :	844 Hour 42 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	34	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.48	kN	No		
HEP :	25.0 %	15.84	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.93	kN	Yes 10	Times	
Ref :		12.67	kN			
LCP :	2.0 %	12.42	kN	Yes 10	Times	
LEP :	25.0 %	9.51	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.07	kN	Min :	2.02	kN	Punch NO.;	16
SD :	4.80	%	Max :	2.57	kN	Punch NO.;	36
Mean Main Pressure :	12.58	kN	Min :	11.71	kN	Punch NO.;	14
SD :	3.40	%	Max :	13.51	kN	Punch NO.;	44
Filling Depth :	Increase ; 11	Times	Decrease ; 12	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	8.97	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.791	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	41
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.62	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.91	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	250056	Tablets			
A.W.C Counter :	248200	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	248198 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	01 Hour 58 Min 15 Sec
Total Counter :	250056	Total Running Time :	844 Hour 42 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.08	kN	No		
HEP :	25.0 %	15.46	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.61	kN	Yes	10 Times	
Ref :		12.37	kN			
LCP :	2.0 %	12.12	kN	Yes	10 Times	
LEP :	25.0 %	9.27	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.89	kN	Min :	1.76	kN	Punch NO.;	8
SD :	1.70	%	Max :	1.99	kN	Punch NO.;	22
Mean Main Pressure :	12.27	kN	Min :	10.17	kN	Punch NO.;	49
SD :	5.40	%	Max :	13.98	kN	Punch NO.;	20
Filling Depth :	Increase ;	5	Times	Decrease ;	8	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.87	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.791	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.20	kN	Max Punch ;	41
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.71	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.90	kN	Max Punch ;	36

Tablet Data (N/A)

Total Counter :	250056	Tablets			
A.W.C Counter :	248200	Tablets			
HEP :	2 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	248198 (100.0%)	Tablets			