

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	03 Hour 09 Min 11 Sec
Total Counter :	400130	Total Running Time :	845 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	34	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.48	kN	No		
HEP :	25.0 %	15.84	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.93	kN	Yes 10	Times	
Ref :		12.67	kN			
LCP :	2.0 %	12.42	kN	Yes 10	Times	
LEP :	25.0 %	9.51	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.87	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	2.09	kN	Min :	2.03	kN	Punch NO.;	41
		3.60	%	Max :	2.53	kN	Punch NO.;	8
Mean Main Pressure :		12.59	kN	Min :	11.11	kN	Punch NO.;	40
	SD :	3.90	%	Max :	13.62	kN	Punch NO.;	44
Filling Depth :	Increase ;	21	Times	Decrease ;	22	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	8.97	mm	Current Cam :	Cam C	
Main Air pressure :	0.778	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	41
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.53	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.75	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	400130	Tablets			
A.W.C Counter :	398296	Tablets			
HEP :	4 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	398292 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pr190041	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	03 Hour 09 Min 11 Sec
Total Counter :	400130	Total Running Time :	845 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	70	%	Manual ;	25	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.500	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.08	kN	No		
HEP :	25.0 %	15.46	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.61	kN	Yes	10 Times	
Ref :		12.37	kN			
LCP :	2.0 %	12.12	kN	Yes	10 Times	
LEP :	25.0 %	9.27	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.66	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.90	kN	Min :	1.78	kN	Punch NO.;	8
SD :	1.60	%	Max :	1.99	kN	Punch NO.;	22
Mean Main Pressure :	12.35	kN	Min :	10.74	kN	Punch NO.;	49
SD :	5.40	%	Max :	13.75	kN	Punch NO.;	20
Filling Depth :	Increase ;	7	Times	Decrease ;	10	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	14	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.87	mm	Current Cam :	Cam C	
Main Air pressure :	0.778	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	13	Min			
Lower Punch Remain Time (S2):	15	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.12	kN		
	Max ;	0.19	kN	Max Punch ;	41
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.52	kN	Max Punch ;	8
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.72	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	400130	Tablets			
A.W.C Counter :	398296	Tablets			
HEP :	4 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	398292 (100.0%)	Tablets			