

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	am98755	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	08 Hour 40 Min 34 Sec
Total Counter :	1100404	Total Running Time :	851 Hour 25 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.92	kN	No		
HEP :	25.0 %	15.30	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.49	kN	Yes	10 Times	
Ref :		12.24	kN			
LCP :	2.0 %	12.00	kN	Yes	10 Times	
LEP :	25.0 %	9.18	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.57	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.19	kN	Min :	2.15	kN	Punch NO.;	28
SD :	0.80	%	Max :	2.24	kN	Punch NO.;	44
Mean Main Pressure :	12.36	kN	Min :	10.96	kN	Punch NO.;	39
SD :	4.10	%	Max :	13.37	kN	Punch NO.;	45
Filling Depth :	Increase ;	138	Times	Decrease ;	122	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	9.04	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.809	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	41
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.20	kN	Max Punch ;	44
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.23	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1100404	Tablets			
A.W.C Counter :	1095117	Tablets			
HEP :	70 (0.0%)	Tablets	LEP :	160 (0.0%)	Tablets
GOOD :	1094887 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	am98755	Batch NO. :	MVM2500613
Print Interval :	50000 Tablets	Running Time :	08 Hour 40 Min 34 Sec
Total Counter :	1100404	Total Running Time :	851 Hour 25 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	51	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.400	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.61	kN	No		
HEP :	25.0 %	15.01	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	12.25	kN	Yes	10	Times
Ref :		12.01	kN			
LCP :	2.0 %	11.77	kN	Yes	10	Times
LEP :	25.0 %	9.01	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	8.41	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.09	kN	Min :	2.06	kN	Punch NO.;	45
SD :	0.80	%	Max :	2.14	kN	Punch NO.;	8
Mean Main Pressure :	12.14	kN	Min :	10.72	kN	Punch NO.;	27
SD :	5.60	%	Max :	13.82	kN	Punch NO.;	20
Filling Depth :	Increase ;	57	Times	Decrease ;	73	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	0	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.95	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.809	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	17	Min			
Lower Punch Remain Time (S2):	19	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	41
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.21	kN	Max Punch ;	44
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.22	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	1100404	Tablets			
A.W.C Counter :	1095117	Tablets			
HEP :	70 (0.0%)	Tablets	LEP :	160 (0.0%)	Tablets
GOOD :	1094887 (100.0%)	Tablets			