

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500813
Print Interval :	50000 Tablets	Running Time :	07 Hour 10 Min 43 Sec
Total Counter :	1004078	Total Running Time :	879 Hour 23 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	52	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.96	kN	No		
HEP :	25.0 %	15.35	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.52	kN	Yes 10	Times	
Ref :		12.28	kN			
LCP :	2.0 %	12.03	kN	Yes 10	Times	
LEP :	25.0 %	9.21	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.59	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.15	kN	Min :	2.10	kN	Punch NO.;	5
SD :	1.00	%	Max :	2.21	kN	Punch NO.;	52
Mean Main Pressure :	12.28	kN	Min :	11.63	kN	Punch NO.;	1
SD :	3.10	%	Max :	13.09	kN	Punch NO.;	16
Filling Depth :	Increase ;	793	Times	Decrease ;	730	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.67	mm	Main Thickness ;	1.68	mm
Filling Depth :	8.79	mm	Current Cam :	Cam C	
Main Air pressure :	0.773	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.26	kN		
	Max ;	0.33	kN	Max Punch ;	17
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	19
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1004078	Tablets			
A.W.C Counter :	1000989	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	6 (0.0%)	Tablets
GOOD :	1000978 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	MEBEV 135 mgSTMV2A00
User ID :	pb97604	Batch NO. :	MVM2500813
Print Interval :	50000 Tablets	Running Time :	07 Hour 10 Min 43 Sec
Total Counter :	1004078	Total Running Time :	879 Hour 23 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	55	%	Manual ;	11	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2000000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.83	kN	No		
HEP :	25.0 %	15.22	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.42	kN	Yes	10 Times	
Ref :		12.18	kN			
LCP :	2.0 %	11.93	kN	Yes	10 Times	
LEP :	25.0 %	9.13	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.52	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.23	kN	Min :	2.19	kN	Punch NO.;	17
SD :	0.70	%	Max :	2.27	kN	Punch NO.;	48
Mean Main Pressure :	12.13	kN	Min :	10.96	kN	Punch NO.;	19
SD :	4.90	%	Max :	13.35	kN	Punch NO.;	15
Filling Depth :	Increase ;	813	Times	Decrease ;	822	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	22	RPM	Capacity :	139920	Tablets/hour
Feeder : Status ;	Auto		Speed ;	12	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.68	mm	Main Thickness ;	1.69	mm
Filling Depth :	8.77	mm	Current Cam :	Cam C	
Main Air pressure :	0.773	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.26	kN		
	Max ;	0.33	kN	Max Punch ;	17
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.22	kN	Max Punch ;	46
Ejection Force :	Average ;	0.04	kN		
	Max ;	0.08	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1004078	Tablets			
A.W.C Counter :	1000989	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	6 (0.0%)	Tablets
GOOD :	1000978 (100.0%)	Tablets			