

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	pb97604	Batch NO. :	PJM2500240
Print Interval :	50000 Tablets	Running Time :	09 Hour 08 Min 16 Sec
Total Counter :	1450822	Total Running Time :	895 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.14	kN	No		
HEP :	25.0 %	29.94	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	24.43	kN	Yes 10	Times	
Ref :		23.95	kN			
LCP :	2.0 %	23.47	kN	Yes 10	Times	
LEP :	25.0 %	17.96	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	16.77	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.83	kN	Min :	1.78	kN	Punch NO.;	32
SD :	1.20	%	Max :	1.89	kN	Punch NO.;	46
Mean Main Pressure :	24.22	kN	Min :	23.10	kN	Punch NO.;	40
SD :	2.50	%	Max :	26.19	kN	Punch NO.;	16
Filling Depth :	Increase ; 7	Times	Decrease ; 38	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	5.82	mm	Current Cam :	Cam B	
Main Air pressure :	0.816	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.36	kN		
	Max ;	0.43	kN	Max Punch ;	52
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	24
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.05	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1450822	Tablets			
A.W.C Counter :	1446634	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1446634 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	pb97604	Batch NO. :	PJM2500240
Print Interval :	50000 Tablets	Running Time :	09 Hour 08 Min 16 Sec
Total Counter :	1450822	Total Running Time :	895 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	35	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.90	kN	No		
HEP :	25.0 %	28.75	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	23.46	kN	Yes 10	Times	
Ref :		23.00	kN			
LCP :	2.0 %	22.54	kN	Yes 10	Times	
LEP :	25.0 %	17.25	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	16.10	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.96	kN	Min :	1.93	kN	Punch NO.;	11
SD :	0.70	%	Max :	2.00	kN	Punch NO.;	47
Mean Main Pressure :	22.85	kN	Min :	20.70	kN	Punch NO.;	53
SD :	3.90	%	Max :	25.38	kN	Punch NO.;	9
Filling Depth :	Increase ; 23	Times	Decrease ; 33	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	9	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	5.51	mm	Current Cam :	Cam B	
Main Air pressure :	0.816	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	8	Min			
Lower Punch Remain Time (S2):	1	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Enable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.36	kN		
	Max ;	0.43	kN	Max Punch ;	52
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	24
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	46

Tablet Data (N/A)

Total Counter :	1450822	Tablets			
A.W.C Counter :	1446634	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	1446634 (100.0%)	Tablets			