

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	yd98913	Batch NO. :	PJM2500340
Print Interval :	50000 Tablets	Running Time :	01 Hour 53 Min 19 Sec
Total Counter :	300168	Total Running Time :	900 Hour 34 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	40	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	29.45	kN	No		
HEP :	25.0 %	28.32	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	23.11	kN	Yes 10	Times	
Ref :		22.65	kN			
LCP :	2.0 %	22.20	kN	Yes 10	Times	
LEP :	25.0 %	16.99	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.86	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.88	kN	Min :	1.83	kN	Punch NO.;	44
SD :	1.00	%	Max :	1.92	kN	Punch NO.;	13
Mean Main Pressure :	22.89	kN	Min :	21.61	kN	Punch NO.;	53
SD :	2.50	%	Max :	24.47	kN	Punch NO.;	45
Filling Depth :	Increase ; 21	Times	Decrease ; 13	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	6.17	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.37	kN		
	Max ;	0.42	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	22
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	300168	Tablets			
A.W.C Counter :	295753	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	295753 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	Prop 40mg STPJ2B00
User ID :	yd98913	Batch NO. :	PJM2500340
Print Interval :	50000 Tablets	Running Time :	01 Hour 53 Min 19 Sec
Total Counter :	300168	Total Running Time :	900 Hour 34 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	39	%	Manual ;	11	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		2000000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.50	kN	No		
HEP :	25.0 %	27.40	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	22.36	kN	Yes 10	Times	
Ref :		21.92	kN			
LCP :	2.0 %	21.48	kN	Yes 10	Times	
LEP :	25.0 %	16.44	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	15.34	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.81	kN	Min :	1.76	kN	Punch NO.;	15
SD :	1.30	%	Max :	1.88	kN	Punch NO.;	14
Mean Main Pressure :	22.20	kN	Min :	20.55	kN	Punch NO.;	1
SD :	3.60	%	Max :	24.00	kN	Punch NO.;	9
Filling Depth :	Increase ; 4	Times	Decrease ; 9	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.55	mm	Main Thickness ;	1.56	mm
Filling Depth :	5.73	mm	Current Cam :	Cam B	
Main Air pressure :	0.748	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	10	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.37	kN		
	Max ;	0.42	kN	Max Punch ;	53
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	22
Ejection Force :	Average ;	0.03	kN		
	Max ;	0.06	kN	Max Punch ;	8

Tablet Data (N/A)

Total Counter :	300168	Tablets			
A.W.C Counter :	295753	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	295753 (100.0%)	Tablets			