

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	01 Hour 27 Min 21 Sec
Total Counter :	200086	Total Running Time :	949 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.69	kN	No		
HEP :	25.0 %	17.97	kN	Yes	10	Rotations
HCP :	2.0 %	14.67	kN	Yes	10	Times
Ref :		14.38	kN			
LCP :	2.0 %	14.09	kN	Yes	10	Times
LEP :	25.0 %	10.78	kN	Yes	10	Rotations
LSP :	30.0 %	10.06	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.25	kN	Min :	4.81	kN	Punch NO.;	21
		5.00	%	Max :	5.90	kN	Punch NO.;	9
Mean Main Pressure :		13.20	kN	Min :	11.78	kN	Punch NO.;	55
	SD :	3.70	%	Max :	14.93	kN	Punch NO.;	23
Filling Depth :	Increase ;	158	Times	Decrease ;	117	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.55	mm	Pre Thickness ;	0.75	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.11	mm	Main Thickness ;	0.62	mm
Filling Depth :	4.69	mm	Current Cam :	Cam B	
Main Air pressure :	0.829	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	17
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	16
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	200086	Tablets			
A.W.C Counter :	184978	Tablets			
HEP :	106 (0.1%)	Tablets	LEP :	12 (0.0%)	Tablets
GOOD :	184860 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500101
Print Interval :	50000 Tablets	Running Time :	01 Hour 27 Min 21 Sec
Total Counter :	200086	Total Running Time :	949 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	10	%	Manual ;	10	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.15	kN	No		
HEP :	25.0 %	18.42	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	15.03	kN	Yes	10 Times	
Ref :		14.73	kN			
LCP :	2.0 %	14.44	kN	Yes	10 Times	
LEP :	25.0 %	11.05	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	10.31	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2 Rotations	
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.16	kN	Min :	4.53	kN	Punch NO.;	38
SD :	6.10	%	Max :	5.94	kN	Punch NO.;	53
Mean Main Pressure :	14.68	kN	Min :	12.67	kN	Punch NO.;	22
SD :	4.80	%	Max :	16.16	kN	Punch NO.;	37
Filling Depth :	Increase ;	82	Times	Decrease ;	85	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	140400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	3.70	mm	Pre Thickness ;	0.71	mm
Main Upper Punch Position ;	3.48	mm			
Main Lower Punch Position ;	4.10	mm	Main Thickness ;	0.62	mm
Filling Depth :	3.91	mm	Current Cam :	Cam B	
Main Air pressure :	0.829	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	22	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.13	kN		
	Max ;	0.20	kN	Max Punch ;	17
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.11	kN	Max Punch ;	16
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.07	kN	Max Punch ;	50

Tablet Data (N/A)

Total Counter :	200086	Tablets			
A.W.C Counter :	184978	Tablets			
HEP :	106 (0.1%)	Tablets	LEP :	12 (0.0%)	Tablets
GOOD :	184860 (99.9%)	Tablets			