

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG,STJU1B00
User ID :	ka98463	Batch NO. :	JUM2500105
Print Interval :	50000 Tablets	Running Time :	00 Hour 43 Min 18 Sec
Total Counter :	72736	Total Running Time :	951 Hour 32 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	10	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
		8.5-14mm			Max :	12.00 mm
Target Quantity :		180000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	31.04	kN	No		
HEP :	25.0 %	29.85	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	24.35	kN	Yes	10	Times
Ref :		23.88	kN			
LCP :	2.0 %	23.40	kN	Yes	10	Times
LEP :	25.0 %	17.91	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	16.71	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	1.66	kN	Min :	1.63	kN	Punch NO.;	28
SD :	0.70	%	Max :	1.68	kN	Punch NO.;	38
Mean Main Pressure :	24.69	kN	Min :	22.80	kN	Punch NO.;	13
SD :	3.70	%	Max :	26.60	kN	Punch NO.;	29
Filling Depth :	Increase ;	39	Times	Decrease ;	22	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.66	mm	Main Thickness ;	1.66	mm
Filling Depth :	9.02	mm	Current Cam :	Cam C	
Main Air pressure :	0.773	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	29	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.07	kN	Max Punch ;	1
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	29
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	72736	Tablets			
A.W.C Counter :	65409	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	65404 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 5 MG,STJU1B00
User ID :	ka98463	Batch NO. :	JUM2500105
Print Interval :	50000 Tablets	Running Time :	00 Hour 43 Min 18 Sec
Total Counter :	72736	Total Running Time :	951 Hour 32 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	49	%	Manual ;	10	RPM
Filling Cam :		Cam C		Cam Range :	Min :	6.50 mm
Target Quantity :		8.5-14mm			Max :	12.00 mm
Air Pressure Low Limit :		180000	Tablets			
Oil Lubrication :		0.000	MPa			
Upper Punch Interval Time(S1) ;		30	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	28.90	kN	No		
HEP :	25.0 %	27.79	kN	Yes	10	Rotations 10 Tablets
HCP :	2.0 %	22.68	kN	Yes	10	Times
Ref :		22.23	kN			
LCP :	2.0 %	21.79	kN	Yes	10	Times
LEP :	25.0 %	16.68	kN	Yes	10	Rotations 10 Tablets
LSP :	30.0 %	15.56	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	1.70	kN	Min :	1.68	kN	Punch NO.;	48
SD :	0.60	%	Max :	1.72	kN	Punch NO.;	19
Mean Main Pressure :	22.30	kN	Min :	19.92	kN	Punch NO.;	52
SD :	4.30	%	Max :	24.31	kN	Punch NO.;	29
Filling Depth :	Increase ;	22	Times	Decrease ;	16	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	3.00	mm			
Pre Lower Punch Position ;	7.00	mm	Pre Thickness ;	4.00	mm
Main Upper Punch Position ;	3.00	mm			
Main Lower Punch Position ;	4.70	mm	Main Thickness ;	1.70	mm
Filling Depth :	8.51	mm	Current Cam :	Cam C	
Main Air pressure :	0.773	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	29	Min			
Lower Punch Remain Time (S2):	8	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.02	kN		
	Max ;	0.08	kN	Max Punch ;	44
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	29
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.09	kN	Max Punch ;	24

Tablet Data (N/A)

Total Counter :	72736	Tablets			
A.W.C Counter :	65409	Tablets			
HEP :	5 (0.0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	65404 (100.0%)	Tablets			