

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	rp98927	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	02 Hour 15 Min 44 Sec
Total Counter :	400176	Total Running Time :	954 Hour 47 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	14.11	kN	No		
HEP :	25.0 %	13.57	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	11.07	kN	Yes	10 Times	
Ref :		10.85	kN			
LCP :	2.0 %	10.64	kN	Yes	10 Times	
LEP :	25.0 %	8.14	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	7.60	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.68	kN	Min :	2.62	kN	Punch NO.;	42
SD :	0.70	%	Max :	2.75	kN	Punch NO.;	24
Mean Main Pressure :	10.82	kN	Min :	9.67	kN	Punch NO.;	50
SD :	5.50	%	Max :	12.16	kN	Punch NO.;	28
Filling Depth :	Increase ;	141	Times	Decrease ;	127	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.38	mm	Current Cam :	Cam B	
Main Air pressure :	0.768	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	45
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	400176	Tablets			
A.W.C Counter :	394295	Tablets			
HEP :	20 (0.0%)	Tablets	LEP :	21 (0.0%)	Tablets
GOOD :	394254 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	rp98927	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	02 Hour 15 Min 44 Sec
Total Counter :	400176	Total Running Time :	954 Hour 47 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.22	kN	No		
HEP :	25.0 %	14.64	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	11.95	kN	Yes 10	Times	
Ref :		11.71	kN			
LCP :	2.0 %	11.48	kN	Yes 10	Times	
LEP :	25.0 %	8.78	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.20	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.56	kN	Min :	2.48	kN	Punch NO.;	19
SD :	1.20	%	Max :	2.63	kN	Punch NO.;	24
Mean Main Pressure :	11.34	kN	Min :	9.55	kN	Punch NO.;	53
SD :	6.00	%	Max :	13.74	kN	Punch NO.;	28
Filling Depth :	Increase ;	100	Times	Decrease ;	101	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.52	mm	Current Cam :	Cam B	
Main Air pressure :	0.768	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	53
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.13	kN	Max Punch ;	45
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	400176	Tablets			
A.W.C Counter :	394295	Tablets			
HEP :	20 (0.0%)	Tablets	LEP :	21 (0.0%)	Tablets
GOOD :	394254 (100.0%)	Tablets			