

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	rp98927	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	03 Hour 56 Min 50 Sec
Total Counter :	700236	Total Running Time :	956 Hour 28 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	107	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.52	kN	No		
HEP :	25.0 %	14.92	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.17	kN	Yes	10 Times	
Ref :		11.94	kN			
LCP :	2.0 %	11.70	kN	Yes	10 Times	
LEP :	25.0 %	8.95	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.35	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.69	kN	Min :	2.66	kN	Punch NO.;	15
SD :	0.70	%	Max :	2.75	kN	Punch NO.;	11
Mean Main Pressure :	11.96	kN	Min :	10.68	kN	Punch NO.;	52
SD :	6.20	%	Max :	14.01	kN	Punch NO.;	29
Filling Depth :	Increase ;	182	Times	Decrease ;	172	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	30	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.60	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.791	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	51
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	700236	Tablets			
A.W.C Counter :	694381	Tablets			
HEP :	46 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	694313 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	rp98927	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	03 Hour 56 Min 50 Sec
Total Counter :	700236	Total Running Time :	956 Hour 28 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		20	Min	Supply Time ;	0.2	Sec
Lower Punch Interval Time(S2) ;		20	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.22	kN	No		
HEP :	25.0 %	14.64	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	11.95	kN	Yes	10 Times	
Ref :		11.71	kN			
LCP :	2.0 %	11.48	kN	Yes	10 Times	
LEP :	25.0 %	8.78	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.20	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.55	kN	Min :	2.50	kN	Punch NO.;	16
SD :	1.10	%	Max :	2.61	kN	Punch NO.;	27
Mean Main Pressure :	11.54	kN	Min :	9.54	kN	Punch NO.;	53
SD :	7.60	%	Max :	13.52	kN	Punch NO.;	2
Filling Depth :	Increase ;	159	Times	Decrease ;	162	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.49	mm	Current Cam :	Cam B	
Main Air pressure :	0.791	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	12	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	43
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	51
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.16	kN	Max Punch ;	11

Tablet Data (N/A)

Total Counter :	700236	Tablets			
A.W.C Counter :	694381	Tablets			
HEP :	46 (0.0%)	Tablets	LEP :	22 (0.0%)	Tablets
GOOD :	694313 (100.0%)	Tablets			