

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	pm98770	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	09 Hour 50 Min 44 Sec
Total Counter :	1750730	Total Running Time :	962 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	109	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.8	Sec
Lower Punch Interval Time(S2) ;		45	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.66	kN	No		
HEP :	25.0 %	15.05	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.28	kN	Yes	10 Times	
Ref :		12.04	kN			
LCP :	2.0 %	11.80	kN	Yes	10 Times	
LEP :	25.0 %	9.03	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.43	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.89	kN	Min :	2.84	kN	Punch NO.;	16
SD :	0.60	%	Max :	2.92	kN	Punch NO.;	51
Mean Main Pressure :	12.03	kN	Min :	10.48	kN	Punch NO.;	36
SD :	5.30	%	Max :	14.25	kN	Punch NO.;	42
Filling Depth :	Increase ;	442	Times	Decrease ;	418	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	31	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.47	mm	Current Cam :	Cam B	
Main Air pressure :	0.806	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	56	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	14
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	39
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	1750730	Tablets			
A.W.C Counter :	1742310	Tablets			
HEP :	331 (0.0%)	Tablets	LEP :	147 (0.0%)	Tablets
GOOD :	1741832 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	pm98770	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	09 Hour 50 Min 44 Sec
Total Counter :	1750730	Total Running Time :	962 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	0.8	Sec
Lower Punch Interval Time(S2) ;		45	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.85	kN	No		
HEP :	25.0 %	15.24	kN	Yes 10	Rotations 10	Tablets
HCP :	2.0 %	12.44	kN	Yes 10	Times	
Ref :		12.20	kN			
LCP :	2.0 %	11.95	kN	Yes 10	Times	
LEP :	25.0 %	9.15	kN	Yes 10	Rotations 10	Tablets
LSP :	30.0 %	8.54	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	2.92	kN	Min :	2.85	kN	Punch NO.;	32
SD :	0.80	%	Max :	2.96	kN	Punch NO.;	42
Mean Main Pressure :	12.13	kN	Min :	9.80	kN	Punch NO.;	38
SD :	7.50	%	Max :	14.28	kN	Punch NO.;	17
Filling Depth :	Increase ;	389	Times	Decrease ;	405	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.41	mm	Current Cam :	Cam B 4.5-10mm	
Main Air pressure :	0.806	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	56	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.03	kN	Max Punch ;	14
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	51
Ejection Force :	Average ;	0.08	kN		
	Max ;	0.13	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	1750730	Tablets			
A.W.C Counter :	1742310	Tablets			
HEP :	331 (0.0%)	Tablets	LEP :	147 (0.0%)	Tablets
GOOD :	1741832 (100.0%)	Tablets			