

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	rp98927	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	16 Hour 01 Min 02 Sec
Total Counter :	2851326	Total Running Time :	968 Hour 33 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	99	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		45	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	15.66	kN	No		
HEP :	25.0 %	15.05	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.28	kN	Yes	10 Times	
Ref :		12.04	kN			
LCP :	2.0 %	11.80	kN	Yes	10 Times	
LEP :	25.0 %	9.03	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.43	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	2.91	kN	Min :	2.83	kN	Punch NO.;	20
SD :	1.00	%	Max :	2.97	kN	Punch NO.;	46
Mean Main Pressure :	12.38	kN	Min :	10.81	kN	Punch NO.;	13
SD :	5.30	%	Max :	13.59	kN	Punch NO.;	1
Filling Depth :	Increase ;	690	Times	Decrease ;	667	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.35	mm	Pre Thickness ;	3.36	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.40	mm	Main Thickness ;	2.41	mm
Filling Depth :	7.16	mm	Current Cam :	Cam B	
Main Air pressure :	0.752	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.01	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	45
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	2851326	Tablets			
A.W.C Counter :	2841937	Tablets			
HEP :	685 (0.0%)	Tablets	LEP :	426 (0.0%)	Tablets
GOOD :	2840826 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	METF 500MG STEW1A00
User ID :	rp98927	Batch NO. :	EWM2505650
Print Interval :	50000 Tablets	Running Time :	16 Hour 01 Min 02 Sec
Total Counter :	2851326	Total Running Time :	968 Hour 33 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	100	%	Manual ;	20	RPM
Filling Cam :		Cam B 4.5-10mm		Cam Range :	Min :	2.50 mm
Target Quantity :		4500000	Tablets		Max :	8.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		120	Min	Supply Time ;	0.5	Sec
Lower Punch Interval Time(S2) ;		45	Min	Supply Time ;	2.2	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	16.38	kN	No		
HEP :	25.0 %	15.75	kN	Yes	10 Rotations	10 Tablets
HCP :	2.0 %	12.85	kN	Yes	10 Times	
Ref :		12.60	kN			
LCP :	2.0 %	12.35	kN	Yes	10 Times	
LEP :	25.0 %	9.45	kN	Yes	10 Rotations	10 Tablets
LSP :	30.0 %	8.82	kN	No		
SD limit :	35.0 %			Yes		
Pre HSP		30.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	3.06	kN	Min :	3.02	kN	Punch NO.;	20
SD :	0.70	%	Max :	3.16	kN	Punch NO.;	31
Mean Main Pressure :	12.77	kN	Min :	10.57	kN	Punch NO.;	52
SD :	6.40	%	Max :	14.75	kN	Punch NO.;	16
Filling Depth :	Increase ;	664	Times	Decrease ;	681	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	28	RPM	Capacity :	178080	Tablets/hour
Feeder : Status ;	Auto		Speed ;	28	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	3.31	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	5.42	mm	Main Thickness ;	2.43	mm
Filling Depth :	6.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.752	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	48	Min			
Lower Punch Remain Time (S2):	4	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.02	kN	Max Punch ;	29
Lower Punch :	Average ;	0.07	kN		
	Max ;	0.12	kN	Max Punch ;	45
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.13	kN	Max Punch ;	51

Tablet Data (N/A)

Total Counter :	2851326	Tablets			
A.W.C Counter :	2841990	Tablets			
HEP :	685 (0.0%)	Tablets	LEP :	426 (0.0%)	Tablets
GOOD :	2840879 (100.0%)	Tablets			