

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500201
Print Interval :	50000 Tablets	Running Time :	00 Hour 10 Min 09 Sec
Total Counter :	19474	Total Running Time :	978 Hour 7 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
		4.5-10mm			Max :	8.00 mm
Target Quantity :		360000	Tablets			
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	17.87	kN	No		
HEP :	25.0 %	17.19	kN	Yes	15	Rotations
HCP :	2.0 %	14.02	kN	Yes	20	Times
Ref :		13.75	kN			
LCP :	2.0 %	13.47	kN	Yes	20	Times
LEP :	25.0 %	10.31	kN	Yes	15	Rotations
LSP :	30.0 %	9.62	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.31	kN	Min :	4.86	kN	Punch NO.;	26
		3.50	%	Max :	5.71	kN	Punch NO.;	53
Mean Main Pressure :		13.79	kN	Min :	12.39	kN	Punch NO.;	26
	SD :	4.00	%	Max :	14.99	kN	Punch NO.;	56
Filling Depth :	Increase ;	13	Times	Decrease ;	1	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	117000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.82	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	0.98	mm
Main Upper Punch Position ;	3.49	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.52	mm
Filling Depth :	3.97	mm	Current Cam :	Cam B	
Main Air pressure :	0.796	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	0
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	16
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.06	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	19474	Tablets			
A.W.C Counter :	12882	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	12882 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	BUME 1MG STJU1A00
User ID :	am98755	Batch NO. :	JUM2500201
Print Interval :	50000 Tablets	Running Time :	00 Hour 10 Min 10 Sec
Total Counter :	19504	Total Running Time :	978 Hour 7 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	15	%	Manual ;	15	RPM
Filling Cam :		Cam B		Cam Range :	Min :	2.50 mm
Target Quantity :		4.5-10mm			Max :	8.00 mm
Air Pressure Low Limit :		360000	Tablets			
Oil Lubrication :		0.000	MPa			
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	18.94	kN	No		
HEP :	25.0 %	18.21	kN	Yes	15	Rotations
HCP :	2.0 %	14.86	kN	Yes	20	Times
Ref :		14.57	kN			
LCP :	2.0 %	14.27	kN	Yes	20	Times
LEP :	25.0 %	10.92	kN	Yes	15	Rotations
LSP :	30.0 %	10.20	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	4.67	kN	Min :	4.43	kN	Punch NO.;	24
SD :	2.70	%	Max :	4.96	kN	Punch NO.;	53
Mean Main Pressure :	14.75	kN	Min :	13.65	kN	Punch NO.;	19
SD :	3.60	%	Max :	15.83	kN	Punch NO.;	52
Filling Depth :	Increase ;	0	Times	Decrease ;	2	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	117000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	2	RPM
Pre Upper Punch Position ;	2.80	mm			
Pre Lower Punch Position ;	3.80	mm	Pre Thickness ;	1.00	mm
Main Upper Punch Position ;	3.50	mm			
Main Lower Punch Position ;	4.01	mm	Main Thickness ;	0.51	mm
Filling Depth :	3.53	mm	Current Cam :	Cam B	
Main Air pressure :	0.797	MPa		4.5-10mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.00	kN		
	Max ;	0.00	kN	Max Punch ;	6
Lower Punch :	Average ;	0.08	kN		
	Max ;	0.10	kN	Max Punch ;	16
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.06	kN	Max Punch ;	5

Tablet Data (N/A)

Total Counter :	19504	Tablets			
A.W.C Counter :	12882	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	12882 (100.0%)	Tablets			