

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	pb97604	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 43 Sec
Total Counter :	50008	Total Running Time :	986 Hour 0 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	75	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.38	kN	No		
HEP :	25.0 %	19.60	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	15.99	kN	Yes 20	Times	
Ref :		15.68	kN			
LCP :	2.0 %	15.37	kN	Yes 20	Times	
LEP :	25.0 %	11.76	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.98	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.09	kN	Min :	4.68	kN	Punch NO.;	10
SD :	3.00	%	Max :	5.44	kN	Punch NO.;	37
Mean Main Pressure :	15.53	kN	Min :	13.87	kN	Punch NO.;	43
SD :	5.30	%	Max :	17.37	kN	Punch NO.;	53
Filling Depth :	Increase ; 20	Times	Decrease ; 31	Times			

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	11	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	7.23	mm	Current Cam :	Cam C	
Main Air pressure :	0.765	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.39	kN	Max Punch ;	26
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	36
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	50008	Tablets			
A.W.C Counter :	44450	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	44450 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	pb97604	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	00 Hour 31 Min 43 Sec
Total Counter :	50008	Total Running Time :	986 Hour 0 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	64	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.000	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.13	kN	No		
HEP :	25.0 %	20.31	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	16.58	kN	Yes 20	Times	
Ref :		16.25	kN			
LCP :	2.0 %	15.93	kN	Yes 20	Times	
LEP :	25.0 %	12.19	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.38	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.31	kN	Min :	5.03	kN	Punch NO.;	27
SD :	2.60	%	Max :	5.64	kN	Punch NO.;	3
Mean Main Pressure :	16.46	kN	Min :	14.69	kN	Punch NO.;	35
SD :	4.30	%	Max :	18.07	kN	Punch NO.;	53
Filling Depth :	Increase ;	20	Times	Decrease ;	5	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	15	RPM	Capacity :	95400	Tablets/hour
Feeder : Status ;	Auto		Speed ;	10	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.45	mm	Current Cam :	Cam C	
Main Air pressure :	0.765	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	14	Min			
Lower Punch Remain Time (S2):	14	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.30	kN		
	Max ;	0.39	kN	Max Punch ;	34
Lower Punch :	Average ;	0.11	kN		
	Max ;	0.14	kN	Max Punch ;	36
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.08	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	50008	Tablets			
A.W.C Counter :	44450	Tablets			
HEP :	0 (0%)	Tablets	LEP :	0 (0%)	Tablets
GOOD :	44450 (100.0%)	Tablets			