

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	pb97604	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	01 Hour 29 Min 24 Sec
Total Counter :	200084	Total Running Time :	986 Hour 58 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.32	kN	No		
HEP :	25.0 %	19.54	kN	Yes	15	Rotations
HCP :	2.0 %	15.94	kN	Yes	20	Times
Ref :		15.63	kN			
LCP :	2.0 %	15.32	kN	Yes	20	Times
LEP :	25.0 %	11.72	kN	Yes	15	Rotations
LSP :	30.0 %	10.94	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	5.19	kN	Min :	4.80	kN	Punch NO.;	22
SD :	2.60	%	Max :	5.47	kN	Punch NO.;	5
Mean Main Pressure :	15.31	kN	Min :	14.11	kN	Punch NO.;	30
SD :	4.30	%	Max :	16.79	kN	Punch NO.;	14
Filling Depth :	Increase ;	85	Times	Decrease ;	104	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	7.16	mm	Current Cam :	Cam C	
Main Air pressure :	0.798	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.22	kN	Max Punch ;	19
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	15
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	200084	Tablets			
A.W.C Counter :	189665	Tablets			
HEP :	71 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	189593 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	pb97604	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	01 Hour 29 Min 24 Sec
Total Counter :	200084	Total Running Time :	986 Hour 58 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	19.94	kN	No		
HEP :	25.0 %	19.18	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	15.65	kN	Yes 20	Times	
Ref :		15.34	kN			
LCP :	2.0 %	15.03	kN	Yes 20	Times	
LEP :	25.0 %	11.51	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	10.74	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	5.14	kN	Min :	4.80	kN	Punch NO.;	17
SD :	2.70	%	Max :	5.39	kN	Punch NO.;	51
Mean Main Pressure :	15.35	kN	Min :	13.73	kN	Punch NO.;	30
SD :	5.50	%	Max :	17.52	kN	Punch NO.;	53
Filling Depth :	Increase ;	79	Times	Decrease ;	64	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.37	mm	Current Cam :	Cam C	
Main Air pressure :	0.798	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	5	Min			
Lower Punch Remain Time (S2):	5	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.23	kN	Max Punch ;	40
Lower Punch :	Average ;	0.13	kN		
	Max ;	0.17	kN	Max Punch ;	15
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	13

Tablet Data (N/A)

Total Counter :	200084	Tablets			
A.W.C Counter :	189665	Tablets			
HEP :	71 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	189593 (100.0%)	Tablets			