

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	ka98463	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	02 Hour 26 Min 42 Sec
Total Counter :	350156	Total Running Time :	987 Hour 55 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.41	kN	No		
HEP :	25.0 %	19.63	kN	Yes	15	Rotations 20 Tablets
HCP :	2.0 %	16.02	kN	Yes	20	Times
Ref :		15.70	kN			
LCP :	2.0 %	15.39	kN	Yes	20	Times
LEP :	25.0 %	11.78	kN	Yes	15	Rotations 20 Tablets
LSP :	30.0 %	10.99	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.23	kN	Min :	4.91	kN	Punch NO.;	10
		4.00	%	Max :	5.92	kN	Punch NO.;	47
Mean Main Pressure :		15.73	kN	Min :	14.21	kN	Punch NO.;	43
	SD :	5.00	%	Max :	18.32	kN	Punch NO.;	7
Filling Depth :	Increase ;	146	Times	Decrease ;	153	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	7.75	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.21	kN	Max Punch ;	42
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	28
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	350156	Tablets			
A.W.C Counter :	339227	Tablets			
HEP :	73 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	339153 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	ka98463	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	02 Hour 26 Min 42 Sec
Total Counter :	350156	Total Running Time :	987 Hour 55 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.10	kN	No		
HEP :	25.0 %	19.33	kN	Yes	15	Rotations
HCP :	2.0 %	15.77	kN	Yes	20	Times
Ref :		15.46	kN			
LCP :	2.0 %	15.15	kN	Yes	20	Times
LEP :	25.0 %	11.60	kN	Yes	15	Rotations
LSP :	30.0 %	10.82	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	5.09	kN	Min :	4.71	kN	Punch NO.;	18
		3.20	%	Max :	5.48	kN	Punch NO.;	8
Mean Main Pressure :		15.24	kN	Min :	13.60	kN	Punch NO.;	31
	SD :	5.20	%	Max :	17.36	kN	Punch NO.;	50
Filling Depth :	Increase ;	105	Times	Decrease ;	93	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	25	RPM	Capacity :	159000	Tablets/hour
Feeder : Status ;	Auto		Speed ;	50	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.46	mm	Current Cam :	Cam C	
Main Air pressure :	0.799	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	9	Min			
Lower Punch Remain Time (S2):	9	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.21	kN	Max Punch ;	42
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.20	kN	Max Punch ;	15
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.09	kN	Max Punch ;	23

Tablet Data (N/A)

Total Counter :	350156	Tablets			
A.W.C Counter :	339227	Tablets			
HEP :	73 (0.0%)	Tablets	LEP :	1 (0.0%)	Tablets
GOOD :	339153 (100.0%)	Tablets			