

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	yd98913	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	10 Hour 23 Min 26 Sec
Total Counter :	1500686	Total Running Time :	995 Hour 53 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	20.95	kN	No		
HEP :	25.0 %	20.15	kN	Yes	15	Rotations 20 Tablets
HCP :	2.0 %	16.44	kN	Yes	20	Times
Ref :		16.12	kN			
LCP :	2.0 %	15.79	kN	Yes	20	Times
LEP :	25.0 %	12.09	kN	Yes	15	Rotations 20 Tablets
LSP :	30.0 %	11.28	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	SD :	5.04	kN	Min :	4.75	kN	Punch NO.;	17
		3.50	%	Max :	5.49	kN	Punch NO.;	38
Mean Main Pressure :		15.92	kN	Min :	14.05	kN	Punch NO.;	15
	SD :	5.70	%	Max :	17.91	kN	Punch NO.;	53
Filling Depth :	Increase ;	534	Times	Decrease ;	474	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.45	mm	Main Thickness ;	1.46	mm
Filling Depth :	7.20	mm	Current Cam :	Cam C	
Main Air pressure :	0.736	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	38
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.56	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.20	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1500686	Tablets			
A.W.C Counter :	1482780	Tablets			
HEP :	1372 (0.1%)	Tablets	LEP :	126 (0.0%)	Tablets
GOOD :	1481282 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 400MGSTIU2B00
User ID :	yd98913	Batch NO. :	IUM2500340
Print Interval :	50000 Tablets	Running Time :	10 Hour 23 Min 26 Sec
Total Counter :	1500686	Total Running Time :	995 Hour 53 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	200	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		2025000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	21.36	kN	No		
HEP :	25.0 %	20.53	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	16.76	kN	Yes 20	Times	
Ref :		16.43	kN			
LCP :	2.0 %	16.10	kN	Yes 20	Times	
LEP :	25.0 %	12.32	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	11.50	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	5.01	kN	Min :	4.74	kN	Punch NO.;	17
		2.60	%	Max :	5.31	kN	Punch NO.;	46
Mean Main Pressure :		16.41	kN	Min :	14.85	kN	Punch NO.;	43
	SD :	4.50	%	Max :	18.11	kN	Punch NO.;	11
Filling Depth :	Increase ;	418	Times	Decrease ;	350	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	20	RPM	Capacity :	127200	Tablets/hour
Feeder : Status ;	Auto		Speed ;	40	RPM
Pre Upper Punch Position ;	2.99	mm			
Pre Lower Punch Position ;	5.50	mm	Pre Thickness ;	2.51	mm
Main Upper Punch Position ;	2.99	mm			
Main Lower Punch Position ;	4.60	mm	Main Thickness ;	1.61	mm
Filling Depth :	7.05	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.736	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	6	Min			
Lower Punch Remain Time (S2):	6	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.14	kN	Max Punch ;	38
Lower Punch :	Average ;	0.15	kN		
	Max ;	0.58	kN	Max Punch ;	15
Ejection Force :	Average ;	0.07	kN		
	Max ;	0.20	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1500686	Tablets			
A.W.C Counter :	1482780	Tablets			
HEP :	1372 (0.1%)	Tablets	LEP :	126 (0.0%)	Tablets
GOOD :	1481282 (99.9%)	Tablets			