

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pm98770	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	04 Hour 32 Min 33 Sec
Total Counter :	505718	Total Running Time :	1004 Hour 29 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	485	%	Manual ;	19	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.53	kN	No		
HEP :	25.0 %	24.55	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.03	kN	Yes 20	Times	
Ref :		19.64	kN			
LCP :	2.0 %	19.24	kN	Yes 20	Times	
LEP :	25.0 %	14.73	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.75	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.12	kN	Min :	7.57	kN	Punch NO.;	31
SD :	3.60	%	Max :	8.77	kN	Punch NO.;	42
Mean Main Pressure :	19.70	kN	Min :	17.99	kN	Punch NO.;	36
SD :	4.00	%	Max :	21.70	kN	Punch NO.;	51
Filling Depth :	Increase ;	229	Times	Decrease ;	238	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	87	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	10.35	mm	Current Cam :	Cam C	
Main Air pressure :	0.796	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.24	kN	Max Punch ;	27
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.19	kN	Max Punch ;	41
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	505718	Tablets			
A.W.C Counter :	497053	Tablets			
HEP :	56 (0.0%)	Tablets	LEP :	196 (0.0%)	Tablets
GOOD :	496801 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pm98770	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	04 Hour 32 Min 33 Sec
Total Counter :	505718	Total Running Time :	1004 Hour 29 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	400	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.00	kN	No		
HEP :	25.0 %	25.96	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.18	kN	Yes 20	Times	
Ref :		20.77	kN			
LCP :	2.0 %	20.35	kN	Yes 20	Times	
LEP :	25.0 %	15.58	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.54	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	7.98	kN	Min :	7.50	kN	Punch NO.;	2
SD :	3.10	%	Max :	8.47	kN	Punch NO.;	42
Mean Main Pressure :	20.76	kN	Min :	19.24	kN	Punch NO.;	44
SD :	4.20	%	Max :	23.19	kN	Punch NO.;	51
Filling Depth :	Increase ;	82	Times	Decrease ;	81	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	72	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	3.45	mm
Filling Depth :	10.39	mm	Current Cam :	Cam C 8.5-14mm	
Main Air pressure :	0.796	MPa			
Oil Lubrication status :					
Upper Punch Remain Time (S1):	3	Min			
Lower Punch Remain Time (S2):	3	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.22	kN	Max Punch ;	1
Lower Punch :	Average ;	0.14	kN		
	Max ;	0.19	kN	Max Punch ;	41
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.08	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	505718	Tablets			
A.W.C Counter :	497053	Tablets			
HEP :	56 (0.0%)	Tablets	LEP :	196 (0.0%)	Tablets
GOOD :	496801 (99.9%)	Tablets			