

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pm98770	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	05 Hour 25 Min 20 Sec
Total Counter :	605774	Total Running Time :	1005 Hour 22 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	485	%	Manual ;	19	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.53	kN	No		
HEP :	25.0 %	24.55	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.03	kN	Yes 20	Times	
Ref :		19.64	kN			
LCP :	2.0 %	19.24	kN	Yes 20	Times	
LEP :	25.0 %	14.73	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.75	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.13	kN	Min :	7.54	kN	Punch NO.;	10
SD :	3.50	%	Max :	8.92	kN	Punch NO.;	4
Mean Main Pressure :	19.80	kN	Min :	18.12	kN	Punch NO.;	4
SD :	4.00	%	Max :	21.47	kN	Punch NO.;	52
Filling Depth :	Increase ;	250	Times	Decrease ;	253	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	87	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	10.53	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.08	kN		
	Max ;	0.24	kN	Max Punch ;	27
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	41
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	605774	Tablets			
A.W.C Counter :	597117	Tablets			
HEP :	56 (0.0%)	Tablets	LEP :	196 (0.0%)	Tablets
GOOD :	596865 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pm98770	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	05 Hour 25 Min 20 Sec
Total Counter :	605774	Total Running Time :	1005 Hour 22 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	400	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		15	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		15	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	27.00	kN	No		
HEP :	25.0 %	25.96	kN	Yes	15	Rotations 20 Tablets
HCP :	2.0 %	21.18	kN	Yes	20	Times
Ref :		20.77	kN			
LCP :	2.0 %	20.35	kN	Yes	20	Times
LEP :	25.0 %	15.58	kN	Yes	15	Rotations 20 Tablets
LSP :	30.0 %	14.54	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	SD :	8.06	kN	Min :	7.28	kN	Punch NO.;	30
		3.90	%	Max :	8.75	kN	Punch NO.;	1
Mean Main Pressure :		21.00	kN	Min :	18.77	kN	Punch NO.;	44
	SD :	4.60	%	Max :	23.75	kN	Punch NO.;	51
Filling Depth :	Increase ;	89	Times	Decrease ;	81	Times		

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	72	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	3.45	mm
Filling Depth :	10.60	mm	Current Cam :	Cam C	
Main Air pressure :	0.807	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	11	Min			
Lower Punch Remain Time (S2):	11	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.07	kN		
	Max ;	0.23	kN	Max Punch ;	52
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.14	kN	Max Punch ;	41
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.08	kN	Max Punch ;	15

Tablet Data (N/A)

Total Counter :	605774	Tablets			
A.W.C Counter :	597117	Tablets			
HEP :	56 (0.0%)	Tablets	LEP :	196 (0.0%)	Tablets
GOOD :	596865 (100.0%)	Tablets			