

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pb97604	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	10 Hour 58 Min 19 Sec
Total Counter :	1205968	Total Running Time :	1010 Hour 56 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	490	%	Manual ;	19	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	25.79	kN	No		
HEP :	25.0 %	24.80	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	20.24	kN	Yes 20	Times	
Ref :		19.84	kN			
LCP :	2.0 %	19.44	kN	Yes 20	Times	
LEP :	25.0 %	14.88	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	13.89	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.09	kN	Min :	7.47	kN	Punch NO.;	6
SD :	4.20	%	Max :	8.70	kN	Punch NO.;	42
Mean Main Pressure :	20.10	kN	Min :	17.88	kN	Punch NO.;	43
SD :	4.40	%	Max :	22.25	kN	Punch NO.;	52
Filling Depth :	Increase ;	321	Times	Decrease ;	343	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	83	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	10.89	mm	Current Cam :	Cam C	
Main Air pressure :	0.728	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	57	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.24	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.22	kN	Max Punch ;	16
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.17	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1205968	Tablets			
A.W.C Counter :	1195974	Tablets			
HEP :	101 (0.0%)	Tablets	LEP :	317 (0.0%)	Tablets
GOOD :	1195556 (100.0%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pb97604	Batch NO. :	IUM2501260
Print Interval :	50000 Tablets	Running Time :	10 Hour 58 Min 19 Sec
Total Counter :	1205968	Total Running Time :	1010 Hour 56 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	410	%	Manual ;	15	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	26.88	kN	No		
HEP :	25.0 %	25.85	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	21.09	kN	Yes 20	Times	
Ref :		20.68	kN			
LCP :	2.0 %	20.27	kN	Yes 20	Times	
LEP :	25.0 %	15.51	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	14.48	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	7.94	kN	Min :	7.16	kN	Punch NO.;	31
SD :	3.90	%	Max :	8.58	kN	Punch NO.;	35
Mean Main Pressure :	20.76	kN	Min :	18.68	kN	Punch NO.;	43
SD :	4.80	%	Max :	23.28	kN	Punch NO.;	51
Filling Depth :	Increase ;	133	Times	Decrease ;	135	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	70	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	3.45	mm
Filling Depth :	10.82	mm	Current Cam :	Cam C	
Main Air pressure :	0.728	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	57	Min			
Lower Punch Remain Time (S2):	27	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	On	

Tightness

Upper Punch :	Average ;	0.10	kN		
	Max ;	0.24	kN	Max Punch ;	1
Lower Punch :	Average ;	0.10	kN		
	Max ;	0.22	kN	Max Punch ;	16
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.17	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	1205968	Tablets			
A.W.C Counter :	1195974	Tablets			
HEP :	101 (0.0%)	Tablets	LEP :	317 (0.0%)	Tablets
GOOD :	1195556 (100.0%)	Tablets			