

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	rp98927	Batch NO. :	IUM2501360
Print Interval :	50000 Tablets	Running Time :	02 Hour 17 Min 23 Sec
Total Counter :	250098	Total Running Time :	1014 Hour 21 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	495	%	Manual ;	19	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	37.48	kN	No		
HEP :	25.0 %	36.04	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	29.41	kN	Yes 20	Times	
Ref :		28.83	kN			
LCP :	2.0 %	28.26	kN	Yes 20	Times	
LEP :	25.0 %	21.62	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	20.18	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.16	kN	Min :	7.50	kN	Punch NO.;	31
SD :	3.90	%	Max :	8.75	kN	Punch NO.;	39
Mean Main Pressure :	28.29	kN	Min :	25.48	kN	Punch NO.;	31
SD :	4.70	%	Max :	31.07	kN	Punch NO.;	45
Filling Depth :	Increase ;	496	Times	Decrease ;	419	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	89	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	11.23	mm	Current Cam :	Cam C	
Main Air pressure :	0.767	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.23	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.25	kN	Max Punch ;	17
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.21	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	250098	Tablets			
A.W.C Counter :	244621	Tablets			
HEP :	47 (0.0%)	Tablets	LEP :	155 (0.1%)	Tablets
GOOD :	244419 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	rp98927	Batch NO. :	IUM2501360
Print Interval :	50000 Tablets	Running Time :	02 Hour 17 Min 23 Sec
Total Counter :	250098	Total Running Time :	1014 Hour 21 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	445	%	Manual ;	50	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	38.75	kN	No		
HEP :	25.0 %	37.26	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	30.41	kN	Yes 20	Times	
Ref :		29.81	kN			
LCP :	2.0 %	29.21	kN	Yes 20	Times	
LEP :	25.0 %	22.36	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	20.87	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	8.07	kN	Min :	7.42	kN	Punch NO.;	10
SD :	3.40	%	Max :	8.56	kN	Punch NO.;	42
Mean Main Pressure :	29.85	kN	Min :	26.62	kN	Punch NO.;	10
SD :	4.40	%	Max :	32.53	kN	Punch NO.;	42
Filling Depth :	Increase ;	230	Times	Decrease ;	194	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	18	RPM	Capacity :	114480	Tablets/hour
Feeder : Status ;	Auto		Speed ;	80	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	3.45	mm
Filling Depth :	10.63	mm	Current Cam :	Cam C	
Main Air pressure :	0.767	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	40	Min			
Lower Punch Remain Time (S2):	12	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.04	kN		
	Max ;	0.21	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.25	kN	Max Punch ;	17
Ejection Force :	Average ;	0.05	kN		
	Max ;	0.21	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	250098	Tablets			
A.W.C Counter :	244621	Tablets			
HEP :	47 (0.0%)	Tablets	LEP :	155 (0.1%)	Tablets
GOOD :	244419 (99.9%)	Tablets			