

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pb97604	Batch NO. :	IUM2501360
Print Interval :	50000 Tablets	Running Time :	06 Hour 15 Min 11 Sec
Total Counter :	700248	Total Running Time :	1018 Hour 19 Min
Station :	Station 1		

Setting Value

Feeder :	Auto ;	495	%	Manual ;	19	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	37.48	kN	No		
HEP :	25.0 %	36.04	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	29.41	kN	Yes 20	Times	
Ref :		28.83	kN			
LCP :	2.0 %	28.26	kN	Yes 20	Times	
LEP :	25.0 %	21.62	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	20.18	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2 Rotations			Calculation Pass :	2	Rotations
Empty Punch No. :	None					

Pressure Data

Mean Pre Pressure :	8.25	kN	Min :	7.51	kN	Punch NO.;	31
SD :	3.60	%	Max :	8.92	kN	Punch NO.;	42
Mean Main Pressure :	29.20	kN	Min :	26.27	kN	Punch NO.;	31
SD :	4.40	%	Max :	32.00	kN	Punch NO.;	42
Filling Depth :	Increase ;	550	Times	Decrease ;	464	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	84	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.35	mm	Main Thickness ;	3.35	mm
Filling Depth :	10.97	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.24	kN	Max Punch ;	52
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	16
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.15	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	700248	Tablets			
A.W.C Counter :	693635	Tablets			
HEP :	53 (0.0%)	Tablets	LEP :	432 (0.1%)	Tablets
GOOD :	693150 (99.9%)	Tablets			

PRODUCTION REPORT

Product Information

Machine Name :	VANTIX P720D	Product Name :	IBUPRO 600MGSTIU2C00
User ID :	pb97604	Batch NO. :	IUM2501360
Print Interval :	50000 Tablets	Running Time :	06 Hour 15 Min 11 Sec
Total Counter :	700248	Total Running Time :	1018 Hour 19 Min
Station :	Station 2		

Setting Value

Feeder :	Auto ;	445	%	Manual ;	50	RPM
Filling Cam :		Cam C 8.5-14mm		Cam Range :	Min :	6.50 mm
Target Quantity :		1350000	Tablets		Max :	12.00 mm
Air Pressure Low Limit :		0.600	MPa			
Oil Lubrication :						
Upper Punch Interval Time(S1) ;		60	Min	Supply Time ;	2.0	Sec
Lower Punch Interval Time(S2) ;		30	Min	Supply Time ;	2.0	Sec
Powder Supply Time :		5.0	Sec			
Initial Reject Time :		2	Tablets			
Upper Punch Tightness High Limit :		1.00	kN			
Lower Punch Tightness High Limit :		4.00	kN			
Ejecting Force High Limit :		4.00	kN			
				Stop Condition ;		
HSP :	30.0 %	38.75	kN	No		
HEP :	25.0 %	37.26	kN	Yes 15	Rotations 20	Tablets
HCP :	2.0 %	30.41	kN	Yes 20	Times	
Ref :		29.81	kN			
LCP :	2.0 %	29.21	kN	Yes 20	Times	
LEP :	25.0 %	22.36	kN	Yes 15	Rotations 20	Tablets
LSP :	30.0 %	20.87	kN	No		
SD limit :	40.0 %			Yes		
Pre HSP		35.00	kN	Yes		
Mean Calculation range :	2	Rotations		Calculation Pass :	2	Rotations
Empty Punch No. :	N					

Pressure Data

Mean Pre Pressure :	7.96	kN	Min :	7.54	kN	Punch NO.;	23
SD :	3.00	%	Max :	8.39	kN	Punch NO.;	38
Mean Main Pressure :	29.76	kN	Min :	27.90	kN	Punch NO.;	23
SD :	3.80	%	Max :	31.89	kN	Punch NO.;	38
Filling Depth :	Increase ;	280	Times	Decrease ;	225	Times	

PRODUCTION REPORT

Operation Value

Disk Speed :	17	RPM	Capacity :	108120	Tablets/hour
Feeder : Status ;	Auto		Speed ;	76	RPM
Pre Upper Punch Position ;	2.00	mm			
Pre Lower Punch Position ;	6.30	mm	Pre Thickness ;	4.30	mm
Main Upper Punch Position ;	2.00	mm			
Main Lower Punch Position ;	5.45	mm	Main Thickness ;	3.45	mm
Filling Depth :	10.52	mm	Current Cam :	Cam C	
Main Air pressure :	0.750	MPa		8.5-14mm	
Oil Lubrication status :					
Upper Punch Remain Time (S1):	45	Min			
Lower Punch Remain Time (S2):	18	Min			
Lower Head Remain Time (S3):	0	Min			
Powder Status :	Disable		Dust Collector :	Off	
Initial Reject :	Off		Buzzer :	Off	

Tightness

Upper Punch :	Average ;	0.09	kN		
	Max ;	0.24	kN	Max Punch ;	1
Lower Punch :	Average ;	0.09	kN		
	Max ;	0.16	kN	Max Punch ;	16
Ejection Force :	Average ;	0.06	kN		
	Max ;	0.15	kN	Max Punch ;	16

Tablet Data (N/A)

Total Counter :	700248	Tablets			
A.W.C Counter :	693688	Tablets			
HEP :	53 (0.0%)	Tablets	LEP :	432 (0.1%)	Tablets
GOOD :	693203 (99.9%)	Tablets			